

BX-Flex Connectors

90° - Squeeze Type - Malleable Iron

Features

- Squeeze type

Applications


- Indoor use only
- In a dry location, use to connect flexible metal conduit, aluminum and steel AC and MC cable to a steel outlet box or other metal enclosure

Standard Material

- Malleable iron

Standard Finish

- Zinc plated



Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/Case	Inches			
						A	B (Min.-Max.)	C	Screws
100M	85239	3/8" 1/2" KO	25	250	40	1.75	.78 - .95	.44	2
101M	10510	1/2"	25	250	40	1.75	.78 - .95	.44	2
102M	10520	3/4"	10	100	30	1.81	.91 - 1.02	.44	2
103M	10530	1"	5	50	30	2.06	1.25 - 1.38	.56	2
104M	10540	1-1/4"	5	20	38	2.81	1.41 - 1.63	.56	2
105M	10550	1-1/2"	---	5	5	3.81	1.75 - 2	.56	2
106M	10560	2"	---	5	10	4.75	2.19 - 2.44	.69	2
107M	10570	2-1/2"	---	5	16	6.25	2.75 - 3	.88	4
108M	10580	3"	---	2	9	7.25	3.25 - 3.50	1	4
109M	10590	3-1/2"	---	1	14	10.25	3.70 - 4.16	1.25	4
110M	10600	4"	---	1	24	13	4.11 - 4.56	1.25	4