

BX-Flex Connectors

90° - Squeeze Type - Zinc



Features


- Squeeze type

Applications

- Indoor use only
- In a dry location, use to connect flexible metallic conduit aluminum and steel AC cable to a steel outlet box, or other metal enclosure
- 3/8" size fits 1/2" knockout
- Suitable for: 3/8" - 3/4" steel and aluminum armored cable, steel and aluminum interlocked metal clad cable, flexible cord, and 1" - 4" flexible metal conduit

Standard Material

- Zinc die cast
- Zinc plated steel strap



Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/Case	Inches			
						A	B (Min.-Max.)	C	Screws
100	10340	3/8" 1/2" KO	50	500	45	1.740	0.43 - 0.72	.370	2
101	10350	1/2"	25	250	35	2.110	0.64 - 1.03	.400	2
102	10360	3/4"	10	100	20	2.400	0.76 - 1.15	.400	2
103	10370	1"	5	50	19	2.870	1.09 - 1.73	.540	2
104	10380	1-1/4"	10	40	20	4.000	1.34 - 1.97	.640	2
105	10390	1-1/2"	---	5	5	6.000	1.65 - 2.61	.750	2
106	10400	2"	---	5	6	6.000	1.54 - 2.54	.740	2
107	10410	2-1/2"	---	5	18	7.187	2.45 - 2.98	.875	4
108	10420	3"	---	2	9	7.875	2.93 - 3.45	1.031	4
109	10430	3-1/2"	---	1	9	9.400	3.28 - 3.95	1.031	4
110	10440	4"	---	1	10	10.200	3.68 - 4.43	1.031	4