

BX-Flex Connectors

90° - Squeeze Type with Insulated Throat - Malleable Iron

Features

- Squeeze type with insulated throat 90°

Applications


- Indoor use only
- In a dry location, use to connect flexible metal conduit, aluminum and steel AC and MC cable to a steel outlet box or other metal enclosure

Standard Material

- Malleable iron

Standard Finish

- Zinc plated



Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/Case	Inches			
						A	B (Min.-Max.)	C	Screws
101Mi	10511	1/2"	25	250	16	1.750	0.78 - 0.95	.440	2
102Mi	10521	3/4"	10	100	30	1.810	0.91 - 1.02	.440	2
103Mi	10531	1"	5	50	60	2.060	1.25 - 1.38	.560	2
104Mi	10541	1-1/4"	5	50	76	2.810	1.41 - 1.63	.560	2
105Mi	10551	1-1/2"	---	5	100	3.810	1.75 - 2.00	.560	2
106Mi	10561	2"	---	5	200	4.750	2.19 - 2.44	.690	2
107Mi	10571	2-1/2"	---	5	320	6.250	2.75 - 3.00	.880	4
108Mi	10581	3"	---	2	450	7.250	3.25 - 3.50	1.000	4
109Mi	10591	3-1/2"	---	1	1400	10.250	3.70 - 4.16	1.250	4
110Mi	10601	4"	---	1	2400	13.000	4.11 - 4.56	1.250	4