

Rigid Offset Nipples

3/4" Offset - Hot Dip Galvanized - Malleable Iron

Features

- NPSM thread: Smooth inside surface to facilitate wire pulling free of damage

Applications

- Indoor or outdoor use
- Use as an offset connector between two enclosures
- Offsets the axis of the raceways by 3/4"

Standard Material

- Malleable iron


Standard Finish

- Hot dip galvanized



E148716

Conforms to finish thickness ASTM
A123/123M
UL 514B
RoHS
NEMA FB 1
Federal Spec. A-A-50553



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	A	Inches B	C
111MHDG	83207	1/2"	10	100	20	2.81	1.02	.75
112MHDG	83208	3/4"	10	100	29	2.75	1.25	.75
113MHDG	83209	1"	10	100	39	2.87	1.56	.75
114MHDG	83211	1-1/4"	5	50	32	3.13	2.00	.75
115MHDG	83213	1-1/2"	5	50	40	3.13	2.31	.75
116MHDG	83215	2"	2	20	21	3.06	2.76	.75
117MHDG	83217	2-1/2"	---	2	3	3.97	3.26	.75
118MHDG	83219	3"	---	2	5	4.43	3.81	.75
119MHDG	83221	3-1/2"	---	1	4	4.82	4.38	.75
119AMHDG	86724	4"	---	1	4	5.04	4.96	.75