

# Intermediate Spacers



## Features

- Resistant to extreme temperature fluctuations
- Available in 16 sizes
- Snap lock design for fast field assembly
- Stays firmly in place during fill
- Heavy duty strut evenly distributes load

## Applications

- Support duct arrays within trenching before encasement
- For use with Topaz Base Spacer

## Standard Material

- High impact polymers



Catalog Number	UPC	Pipe Size	Separation	Ship Case	Weight/Case
<b>1331</b>	23326	<b>4</b>	1"	200	46
<b>1332</b>	23327	<b>2</b>	1-1/2"	500	50
<b>1333</b>	23328	<b>3</b>	1-1/2"	250	35
<b>1334</b>	23329	<b>4</b>	1-1/2"	180	49
<b>1335</b>	23330	<b>5</b>	1-1/2"	140	35
<b>1336</b>	23331	<b>6</b>	1-1/2"	100	28
<b>1337</b>	23332	<b>2</b>	2"	325	36
<b>1338</b>	23333	<b>3</b>	2"	225	35
<b>1339</b>	23334	<b>4</b>	2"	160	37
<b>1340</b>	23335	<b>5</b>	2"	100	36
<b>1341</b>	23336	<b>6</b>	2"	100	31
<b>1342</b>	23337	<b>2</b>	3"	275	39
<b>1343</b>	23338	<b>3</b>	3"	160	30
<b>1344</b>	23339	<b>4</b>	3"	125	33
<b>1345</b>	23340	<b>5</b>	3"	90	28
<b>1346</b>	23341	<b>6</b>	3"	75	26