

Base Spacers



Features

- Proven base plate design maintains consistent vertical separation between trench floor and first duct tier
- Two-piece interlock design eliminates banding
- Resistant to extreme temperature fluctuations
- Available in 16 sizes
- Snap lock design for fast field assembly
- Stays firmly in place during fill
- Heavy duty strut evenly distributes load

Applications

- Support duct arrays within trenching before encasement
- For use with Topaz Intermediate Spacers

Standard Material

- High impact polymers

Catalog Number	UPC	Pipe Size	Separation	Ship Case	Weight/ Case
1347	23342	4	1"	250	50
1348	23343	2	1-1/2"	450	65
1349	23344	3	1-1/2"	250	48
1350	23345	4	1-1/2"	180	47
1351	23346	5	1-1/2"	140	43
1352	23347	6	1-1/2"	100	33
1353	23348	2	2"	325	48
1354	23349	3	2"	225	44
1355	23350	4	2"	180	47
1356	23351	5	2"	100	32
1357	23352	6	2"	100	34
1358	23353	2	3"	300	48
1359	23354	3	3"	190	41
1360	23355	4	3"	150	43
1361	23356	5	3"	90	30
1362	23357	6	3"	90	32

All base spacers give a three inch separation between the bottom row of ducts and the trench floor- with the exception of the 4" x 1" spacer which provides a 1-1/4" separation.