

BX-Flex Connectors

Straight - Squeeze Type - Malleable Iron

Features

- Squeeze type straight

Applications


- Indoor use only
- In a dry location, use to connect flexible metallic conduit and steel AC cable to a steel outlet box, load center or other metal enclosure
- The 3/8" can also be used with steel and aluminum MC cable
- 3/8" size fits 1/2" knockout
- Suitable for: 3/8" steel flexible conduit, #14-2 metal conduit and #4-2 wire steel armored cable, 3/4" steel flexible metal conduit and #6-3 wire steel armored cable, 1" steel and reduced wall steel flexible metal conduit and #2-2 wire steel armored cable and 1-1/4" - 4" steel flexible metal conduit

Standard Material

- Malleable iron

Standard Finish

- Zinc plated



Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/Case	Inches			
						A	B (Min.-Max.)	C	Screws
150M	83748	3/8" 1/2" KO	25	250	30	.93	.55 - .60	.50	1
151M	11100	1/2"	25	250	30	.94	.78 - .94	.50	1
152M	11110	3/4"	25	250	48	1.13	.91 - 1.08	.50	1
153M	11120	1"	10	100	26	1.19	1.28 - 1.44	.56	1
154M	11130	1-1/4"	10	100	39	1.25	1.44 - 1.63	.63	1
155M	11140	1-1/2"	5	50	33	1.88	1.63 - 1.88	.69	1
156M	11150	2"	---	20	21	2	2.19 - 2.38	.75	1
157M	11160	2-1/2"	---	10	14	2.06	2.70 - 2.95	.94	2
158M	11170	3"	---	2	4	2.25	3.13 - 3.50	.94	2
159M	11180	3-1/2"	---	1	5	3.56	3.72 - 4	1.25	2
160M	11190	4"	---	1	7	3.69	4.06 - 4.44	1.25	2