

# Parallel Conduit Support

## Hot Dip Galvanized

### Features

- Hot dip galvanized for added durability and corrosion protection
- Provides a secure connection and tight clamping action capable of withstanding heavy load

### Applications

- Parallel conduit supports are used to mount EMT, Rigid or IMC conduit parallel to a beam, channel or angle support

### Standard Material

- Malleable iron
- Galvanized steel hardware


### Standard Finish

- Hot dip galvanized



E174011

Conforms to finish thickness  
ASTM A123/123M  
UL 2239  
RoHS  
NEMA FB1  
Federal Spec. A-A-50553



Catalog Number	UPC	Size	Ship Case	Weight/Case	Inches	
					A	B
<b>1561HDG</b>	83233	<b>1/2"</b>	50	29	2.80	1.42
<b>1562HDG</b>	83235	<b>3/4"</b>	50	32	2.99	1.47
<b>1563HDG</b>	83236	<b>1"</b>	50	35	3.19	1.54
<b>1564HDG</b>	86554	<b>1-1/4"</b>	25	18	3.39	2.01
<b>1565HDG</b>	86555	<b>1-1/2"</b>	25	24	3.62	2.01
<b>1566HDG</b>	86556	<b>2"</b>	25	25	4.37	2.87
<b>1567HDG</b>	86557	<b>2-1/2"</b>	10	14	5.12	3.23
<b>1568HDG</b>	86558	<b>3"</b>	10	16	5.79	4.06
<b>1569HDG</b>	86559	<b>3-1/2"</b>	10	19	6.26	4.53
<b>1570HDG</b>	86560	<b>4"</b>	10	22	6.46	4.61