

# BX-Flex Connectors

## Straight - Squeeze Type with insulated Throat- Malleable Iron

### Features

- Squeeze type straight with insulated throat

### Applications


- Indoor use only
- In a dry location, use to connect flexible metallic conduit and steel AC cable to a steel outlet box, load center or other metal enclosure
- Suitable for: 1/2" steel flexible conduit, #14/2 metal conduit and #4-2 wire steel armored cable, 3/4" steel flexible metal conduit and #6-3 wire steel armored cable, 1" steel and reduced wall steel flexible metal conduit and #2-2 wire steel armored cable and 1-1/4" - 4" steel flexible metal conduit

### Standard Material

- Malleable iron

### Standard Finish

- Zinc plated



Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/Case	Inches			
						A	B (Min.-Max.)	C	Screws
<b>151Mi</b>	11101	<b>1/2"</b>	25	250	12	0.94	0.78 - 0.94	0.50	1
<b>152Mi</b>	11111	<b>3/4"</b>	25	250	19	1.13	0.91 - 1.08	0.50	1
<b>153Mi</b>	11121	<b>1"</b>	10	100	26	1.19	1.28 - 1.44	0.56	1
<b>154Mi</b>	11131	<b>1-1/4"</b>	10	100	39	1.25	1.44 - 1.63	0.63	1
<b>155Mi</b>	11141	<b>1-1/2"</b>	5	50	66	1.88	1.63 - 1.88	0.69	1
<b>156Mi</b>	11151	<b>2"</b>	---	20	105	2.00	2.19 - 2.38	0.75	1
<b>157Mi</b>	11161	<b>2-1/2"</b>	---	10	150	2.06	2.70 - 2.95	0.94	2
<b>158Mi</b>	11171	<b>3"</b>	---	2	200	2.25	3.13 - 3.50	0.94	2
<b>159Mi</b>	11181	<b>3-1/2"</b>	---	1	500	3.56	3.72 - 4.00	1.25	2
<b>160Mi</b>	11191	<b>4"</b>	---	1	700	3.69	4.06 - 4.44	1.25	2