

# BX-Flex Connectors

## Straight - Squeeze Type - Zinc Die Cast

### Features


- Squeeze type straight
- Available with insulated throat

### Applications

- Indoor use only
- In a dry location, use to connect flexible metallic conduit and steel AC cable to a steel outlet box, load center or other metal enclosure
- The 3/8" can also be used with steel and aluminum MC cable
- 3/8" size fits 1/2" knockout
- Suitable for: 3/8" steel flexible conduit, #14/2 metal conduit and #4-2 wire steel armored cable, 3/4" steel flexible metal conduit and #6-3 wire steel armored cable, 1" steel and reduced wall steel flexible metal conduit and #2-2 wire steel armored cable and 1-1/4" - 4" steel flexible metal conduit

### Standard Material

- Zinc die cast



Catalog Number	UPC	Conduit Size	Unit Carton	Ship Case	Weight/Case	Inches			
						A	B (Min.-Max.)	C	Screws
<b>150</b>	10990	<b>3/8" 1/2" KO</b>	50	500	35	1.00	0.58-0.61	.370	1
<b>151</b>	11000	<b>1/2"</b>	25	250	25	1.47	0.74-0.95	.400	1
<b>152</b>	11010	<b>3/4"</b>	25	250	32	1.58	0.88-1.11	.400	1
<b>153</b>	11020	<b>1"</b>	10	100	20	1.75	1.14-1.38	.540	1
<b>154</b>	11030	<b>1-1/4"</b>	10	100	29	1.91	1.42-1.65	.640	1
<b>155</b>	11040	<b>1-1/2"</b>	5	50	20	2.09	1.68-1.94	.750	1
<b>156</b>	11050	<b>2"</b>	10	40	21	2.34	2.08-2.56	.740	1
<b>157</b>	11060	<b>2-1/2"</b>	---	10	9	2.81	2.85-3.25	.875	2
<b>158</b>	11070	<b>3"</b>	---	10	17	3.84	3.33-3.63	1.03	2
<b>159</b>	11080	<b>3-1/2"</b>	---	1	3	4.19	3.75-4.10	1.03	2
<b>160</b>	11090	<b>4"</b>	---	1	3	4.56	4.18-4.58	1.03	2