

# Rigid Watertight Hubs

## Insulated Throat - Malleable Iron

### Features

- Flame-retardant insulated throat
- Male hub thread - NPT
- Female thread for Rigid conduit and IMC-NPT
- Recessed o-ring assures watertight and dust tight connections
- Type NHUB with insulated throat and bonding locknut is suitable for service entrance applications
- RoHS compliant

### Applications


- Indoor or outdoor use
- Use to connect Rigid or IMC conduit to a load center or other metal enclosure where a watertight joint is required at knockouts or slip-fit holes

### Standard Material

- Malleable iron

### Standard Finish

- Zinc plated



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/ Case	Inches	
						A	B
<b>201M</b>	11552	<b>1/2"</b>	25	250	49	1.31	1.54
<b>202M</b>	11562	<b>3/4"</b>	10	100	29	1.37	1.73
<b>203M</b>	11572	<b>1"</b>	10	100	29	1.59	2.04
<b>204M</b>	11582	<b>1-1/4"</b>	2	20	15	1.59	2.42
<b>205M</b>	11592	<b>1-1/2"</b>	2	20	16	1.59	2.79
<b>206M</b>	11602	<b>2"</b>	2	20	18	1.59	3.30
<b>207M</b>	11612	<b>2-1/2"</b>	---	2	4	2.44	3.70
<b>208M</b>	11622	<b>3"</b>	---	2	5	2.44	4.39
<b>209M</b>	11623	<b>3-1/2"</b>	---	5	5	2.44	4.88
<b>210M</b>	11632	<b>4"</b>	---	1	6	2.44	5.50
<b>210MA</b>	85555	<b>5"</b>	---	1	3	3.50	6.80
<b>210MB</b>	85556	<b>6"</b>	---	1	6	3.59	8.18