

# Rigid Locknuts

## Steel

### Features

- Tightens without deformation

### Applications


- To connect externally threaded conduit connector to a threadless opening in a box or enclosure

### Standard Material

- Steel

### Standard Finish

- Zinc plated



Catalog Number	UPC	Size	Threads Per Inch	Unit Carton	Ship Case	Weight/Case	Inches		
							A	B	Thread Pitch Diameter
<b>281</b>	12300	<b>1/2"</b>	14	100	2000	20	1.15	.110	.787 - .797
<b>282</b>	12310	<b>3/4"</b>	14	100	1000	20	1.45	.115	.999 - 1.009
<b>283</b>	12320	<b>1"</b>	11-1/2	100	1000	30	1.75	.140	1.250 - 1.260
<b>284</b>	12330	<b>1-1/4"</b>	11-1/2	50	500	20	2.10	.140	1.595 - 1.605
<b>285</b>	12340	<b>1-1/2"</b>	11-1/2	50	500	30	2.40	.140	1.837 - 1.847
<b>286</b>	12350	<b>2"</b>	11-1/2	25	250	20	2.95	.140	2.307 - 2.317
<b>287</b>	12360	<b>2-1/2"</b>	8	---	50	6	3.55	.185	2.777 - 2.788
<b>288</b>	12370	<b>3"</b>	8	---	50	9	3.55	.190	3.403 - 3.414
<b>289</b>	12380	<b>3-1/2"</b>	8	---	25	6	4.20	.190	3.892 - 3.904
<b>290</b>	12390	<b>4"</b>	8	---	25	7	4.75	.190	4.399 - 4.411
<b>290A</b>	12400	<b>5"</b>	8	---	10	5	6.67	.380	5.488 - 5.500
<b>290B</b>	12410	<b>6"</b>	8	---	10	8	7.93	.400	6.545 - 6.557