

Rigid Locknuts

UL Listed - Steel

Features

- Tightens without deformation
- UL listed

Applications


- To connect externally threaded conduit connector to a threadless opening in a box or enclosure

Standard Material

- Steel

Standard Finish

- Zinc plated



Catalog Number	UPC	Size	Threads Per Inch	Unit Carton	Ship Case	Weight/Case	Inches		
							A	B	Thread Pitch Diameter
281UL	86392	1/2"	14	200	2000	23	1.15	.110	.787 - .797
282UL	86393	3/4"	14	100	1000	23	1.45	.115	.999 - 1.009
283UL	86394	1"	11-1/2	100	1000	33	1.75	.140	1.250 - 1.260
284UL	86395	1-1/4"	11-1/2	50	500	23	2.10	.140	1.595 - 1.605
285UL	86396	1-1/2"	11-1/2	50	500	33	2.40	.140	1.837 - 1.847
286UL	86397	2"	11-1/2	25	250	23	2.95	.140	2.307 - 2.317
287UL	86398	2-1/2"	8	---	50	8	3.55	.185	2.777 - 2.788
288UL	86399	3"	8	---	50	12	3.55	.190	3.403 - 3.414
289UL	86400	3-1/2"	8	---	25	9	4.20	.190	3.892 - 3.904
290UL	86401	4"	8	---	25	10	4.75	.190	4.399 - 4.411