

Compression Lugs

One Hole - Long Barrel

Features

- Produced from high conductivity copper tubing and suitable for heavy duty applications
- Tin-plated to provide corrosion resistance
- Color coded

Applications


- Listed for 35 KV maximum when properly installed
- Ideal for direct burial in earth or concrete and grounding applications

Standard Material

- Copper

Standard Finish

- Tin plated



Catalog Number	UPC	Wire Size	Color Code	Bolt Size	Unit Carton	Ship Case	Weight/Case	Inches	
								A	B
3001	41050	#8	Red	1/4"	100	1000	32	1.70	.38
3002	41051	#6	Blue	1/4"	100	1000	32	1.77	.38
3003	41052	#4	Gray	1/4"	100	1000	32	1.77	.50
3005	41054	#2	Brown	3/8"	50	500	32	2.00	.67
3005A	81808	#1	Green	3/8"	50	500	32	2.09	.67
3006	41055	1/0	Pink	3/8"	50	500	18	2.20	.75
3007	41056	2/0	Black	3/8"	25	250	18	2.80	.75
3008	41057	3/0	Orange	3/8"	25	250	10	2.80	.87
3008A	81809	3/0	Orange	1/2"	25	250	10	2.80	.87
3009	41058	4/0	Purple	1/2"	25	250	10	2.80	1.00
3009A	41059	250 MCM	Yellow	1/2"	20	200	10	3.03	1.13
3009B	41061	300 MCM	White	1/2"	10	100	10	3.39	1.13
3010	41062	350 MCM	Red	1/2"	10	100	8	3.50	1.13
3010A	41063	400 MCM	Blue	1/2"	10	100	8	3.74	1.34
3011	41064	500 MCM	Brown	1/2"	5	50	8	4.02	1.50
3011A	41065	600 MCM	Green	5/8"	5	50	8	4.25	1.75
3012	41066	750 MCM	Black	5/8"	5	50	8	5.16	1.87