

# Rigid Capped Bushings

## Steel Cap

### Features


- Steel cap is used inside bushing to prevent debris from entering conduit

### Applications

- Indoor or outdoor use
- Use with locknut to terminate threaded Rigid or IMC conduit to an outlet box

### Standard Material

- Zinc die cast with steel cap



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches	
						A	B
<b>301CB</b>	12531	<b>1/2"</b>	100	1000	5	1.053	.37
<b>302CB</b>	12541	<b>3/4"</b>	100	1000	7	1.327	.37
<b>303CB</b>	12551	<b>1"</b>	50	500	11	1.584	.37
<b>304CB</b>	12561	<b>1-1/4"</b>	25	250	17	1.952	.50
<b>305CB</b>	12571	<b>1-1/2"</b>	25	250	21	2.201	.52
<b>306CB</b>	12581	<b>2"</b>	25	1000	34	2.693	.52
<b>307CB</b>	12591	<b>2-1/2"</b>	10	100	48	3.235	.85
<b>308CB</b>	12601	<b>3"</b>	10	100	61	3.855	.85
<b>309CB</b>	12611	<b>3-1/2"</b>	---	10	70	4.359	.85
<b>310CB</b>	12631	<b>4"</b>	---	10	125	5.011	.85
<b>310ACB</b>	12621	<b>5"</b>	---	10	78	6.15	1.30
<b>310BCB</b>	85152	<b>6"</b>	---	10	85	7.25	1.125