

# Rigid Conduit Bushings

## Malleable Iron

### Features


- Rounded surface of the bushing prevents damage to wire insulation

### Applications

- Indoor or outdoor use
- Use with locknut to terminate threaded Rigid or IMC conduit to an outlet box

### Standard Material

- Malleable iron



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches	
						A	B
<b>301M</b>	12630	<b>1/2"</b>	100	1000	50	1.223	.48
<b>302M</b>	12640	<b>3/4"</b>	50	500	30	1.498	.49
<b>303M</b>	12650	<b>1"</b>	50	500	24	1.818	.56
<b>304M</b>	12660	<b>1-1/4"</b>	25	250	30	2.423	.61
<b>305M</b>	12670	<b>1-1/2"</b>	---	25	22	2.512	.68
<b>306M</b>	12680	<b>2"</b>	---	25	35	3.053	.68
<b>307M</b>	12690	<b>2-1/2"</b>	---	15	20	3.624	.85
<b>308M</b>	12700	<b>3"</b>	---	10	10	4.172	.91
<b>309M</b>	12710	<b>3-1/2"</b>	---	10	13	4.767	1.00
<b>310M</b>	12720	<b>4"</b>	---	10	20	5.321	1.06
<b>310AM</b>	12622	<b>5"</b>	---	10	25	6.15	1.30
<b>310BM</b>	12623	<b>6"</b>	---	10	35	7.19	1.30