

Compression Lug Splices

Long Barrel



Features

- Seamless, high conductivity copper tubing, suitable for heavy duty applications
- Tin-plated to provide corrosion resistance
- Color coded

Applications

- Suitable for use at voltages up to 35 KV provided connector is properly taped
- 5 KV is the maximum voltage in all bare splice applications




Standard Material

- Copper

Standard Finish

- Tin plated



Catalog Number	UPC	Wire Size	Color Code	Unit Carton	Ship Case	Weight/Case	Inches	
							A	B
3101	41080	#8	Red	100	1000	32	1.75	.20
3102	41081	#6	Blue	100	1000	32	1.75	.20
3103	41082	#4	Gray	100	1000	32	1.75	.25
3105	41084	#2	Brown	50	500	32	1.90	.31
3106	41085	1/0	Pink	25	250	18	2.20	.39
3107	41086	2/0	Black	25	250	18	2.25	.44
3108	41087	3/0	Orange	25	250	18	2.25	.49
3109	41088	4/0	Purple	25	250	10	2.75	.55
3109A	41089	250 MCM	Yellow	10	100	10	3.25	.59
3109B	41090	300 MCM	White	10	100	10	3.50	.66
3110	41091	350 MCM	Red	10	100	12	3.75	.70
3110A	41092	400 MCM	Blue	10	100	12	3.75	.76
3111	41093	500 MCM	Brown	5	50	12	4.25	.83
3111A	81810	600 MCM	Green	5	50	14	4.50	.93
3112	81811	750 MCM	Black	5	50	14	4.75	1.03