

Insulated Metallic Grounding Bushings

With Aluminum Lug - 105°C Thermoplastic Liner - Zinc

Features

- Liner is rated flame retardant to 105°C
- UL listed for use with copper or aluminum grounding conductor

Applications


- Indoor or outdoor use
- Use with locknut to terminate service conduit to a cabinet
- Lug provided for bonding jumper to a neutral bus bar
- Round surface of bushing prevents damage to wire insulation
- Plastic liner prevents damage to wire insulation

Standard Material

- Body - Zinc/plastic insulator
- Lug - Aluminum
- Clamping screw - Steel
- Set screws - Steel



E195122



Catalog Number	UPC	Size	Grounding Lug Wire Size		Unit Carton	Ship Case	Weight/Case	Inches	
			Min.	Max.				A	B
321	12930	1/2"	14	4	50	500	25	1.25	.50
322	12940	3/4"	14	4	50	500	35	1.50	.50
323	12950	1"	14	4	25	250	30	1.75	.56
324	12960	1-1/4"	14	4	20	200	34	2.12	.62
325	12970	1-1/2"	14	2	10	100	20	2.37	.75
326	12980	2"	14	2	10	100	35	2.81	.75
327	12990	2-1/2"	14	1/0	--	50	25	3.62	.93
328	13000	3"	14	1/0	---	10	6	4.18	.93
329	13010	3-1/2"	14	2/0	---	10	7	4.68	.93
330	13020	4"	6	250MCM	---	10	8	5.25	.93