

Insulated Metallic Grounding Bushings

With Aluminum Lug - 105°C Thermoplastic Liner - Malleable Iron



Features


- Liner is rated flame retardant to 105°C
- UL listed for use with copper or aluminum grounding conductor

Applications

- Indoor or outdoor use (aluminum lug)
- Use with locknut to terminate service conduit to a cabinet
- Lug provided for bonding jumper to a neutral bus bar
- Round surface of bushing prevents damage to wire insulation
- Plastic liner prevents damage to wire insulation

Standard Material

- Body - Malleable iron
- Plastic insulator
- Lug - Aluminum
- Clamping screw - Steel
- Set screws - Steel



Catalog Number	UPC	Size	Grounding Lug Wire Size		Unit Carton	Ship Case	Weight/Case	Inches	
			Min.	Max.				A	B
321M	13030	1/2"	14	4	50	500	25	1.25	.50
322M	13040	3/4"	14	4	50	500	30	1.48	.54
323M	13050	1"	14	4	25	250	23	1.80	.65
324M	13060	1-1/4"	14	4	20	200	34	2.40	.73
325M	13070	1-1/2"	14	2	25	250	53	2.50	.80
326M	13080	2"	14	2	25	250	78	3.03	.80
327M	13090	2-1/2"	14	1/0	---	10	4	3.60	.95
328M	13100	3"	14	1/0	---	10	5	4.16	1.03
329M	13110	3-1/2"	14	2/0	---	10	15	4.75	1.15
330M	13120	4"	14	2/0	---	10	20	5.30	1.17
330AM	13122	5"	6	250MCM	---	10	25	6.15	1.130
330BM	13124	6"	6	250MCM	---	10	35	7.19	1.130