

Insulated Metallic Grounding Bushings With Aluminum Lay-In Lug - Hot Dip Galvanized Malleable Iron

Features

- Hot dip galvanized for superior protection against corrosion
- Tin plated aluminum alloy 6061-T6 rated for AL and CU conductor
- Liner is rated flame retardant to 105°C
- UL listed for use with copper or aluminum grounding conductor

Applications

- Use to provide a means of grounding Rigid or IMC conduit
- Indoor or outdoor use (aluminum lug)
- Use with locknut to terminate service conduit to a cabinet
- Lug provided for bonding jumper to a neutral bus bar
- Round surface of bushing prevents damage to wire insulation
- Plastic liner prevents damage to wire insulation

Standard Material

- Body - Malleable iron
- Plastic insulator
- Lug - Aluminum
- Clamping screw - Steel
- Set screws - Steel


Standard Finish

- Hot dip galvanized



E195122

Conforms to finish thickness ASTM
A123/123M
UL 514B and UL 467
RoHS
NEMA FB 1
Federal Spec. A-A-50553



Catalog Number	UPC	Size	Grounding Lug Wire Size		Unit Carton	Ship Case	Weight/Case	Inches	
			Min.	Max.				A	B
331MHDG	86684	1/2"	14	4	50	500	45	1.08	.57
332MHDG	86685	3/4"	14	4	50	500	50	1.31	.57
333MHDG	86686	1"	14	4	25	250	32	1.61	.65
334MHDG	86688	1-1/4"	14	4	20	200	36	1.91	.71
335MHDG	86690	1-1/2"	14	4	10	100	25	2.16	.73
336MHDG	86692	2"	14	4	10	100	30	2.72	.73
337MHDG	86693	2-1/2"	14	1/0	5	50	25	3.23	.94
338MHDG	86695	3"	14	1/0	---	25	18	3.88	.94
339MHDG	86697	3-1/2"	14	1/0	---	10	20	4.43	.94
340MHDG	86699	4"	14	1/0	---	10	24	4.89	.94
340ALMHDG	86701	5"	6	250 MCM	---	10	27	6.10	1.14
340BLMHDG	86702	6"	6	250 MCM	---	10	32	7.15	1.14