

Insulated Metallic Grounding Bushings With Aluminum Lay-In Lug - Malleable Iron

Features

- Liner is rated flame retardant to 105°C
- UL listed for use with copper or aluminum grounding conductor

Applications


- Indoor or outdoor use (aluminum lug)
- Use with locknut to terminate service conduit to a cabinet
- Lug provided for bonding jumper to a neutral bus bar
- Round surface of bushing prevents damage to wire insulation
- Plastic liner prevents damage to wire insulation

Standard Material

- Body - Malleable iron
- Plastic insulator
- Lug - Aluminum
- Clamping screw - Steel
- Set screws - Steel

Standard Finish

- Body - Zinc plated



Catalog Number	UPC	Size	Grounding Lug Wire Size		Unit Carton	Ship Case	Weight/Case	Inches	
			Min.	Max.				A	B
331M	13300	1/2"	14	4	50	500	45	1.08	.57
332M	13310	3/4"	14	4	50	500	50	1.31	.57
333M	13320	1"	14	4	25	250	40	1.61	.65
334M	13330	1-1/4"	14	4	20	200	35	1.91	.71
334AM	13340	1-1/4"	14	1/0	20	200	35	1.91	.71
335M	13350	1-1/2"	14	4	10	100	25	2.16	.73
335AM	13360	1-1/2"	14	1/0	10	100	25	2.16	.73
336M	13370	2"	14	4	10	100	30	2.72	.73
336AM	13380	2"	14	1/0	10	100	30	2.72	.73
337M	13390	2-1/2"	14	1/0	---	50	25	3.23	.94
337AM	13400	2-1/2"	6	250 MCM	---	50	25	3.23	.94
338M	13410	3"	14	1/0	---	25	18	3.88	.94
338AM	13420	3"	6	250 MCM	---	25	18	3.88	.94
339M	13430	3-1/2"	14	1/0	---	10	20	4.43	.94
339AM	13440	3-1/2"	6	250 MCM	---	10	20	4.43	.94
340M	13450	4"	14	1/0	---	10	25	4.89	.94
340AM	13460	4"	6	250 MCM	---	10	25	4.89	.94
340ALM	13462	5"	6	250 MCM	---	10	25	6.10	1.14
340BLM	13463	6"	6	250 MCM	---	10	35	7.15	1.14