

Insulated Metallic Grounding Bushings

With Aluminum Lay-In Lug - Zinc Die Cast

Features

- Tin plated aluminum alloy 6061-T6 rated for AL and CU conductor
- Liner is rated flame retardant to 105°C
- UL listed for use with copper or aluminum grounding conductor

Applications


- Use to provide a means of grounding Rigid or IMC conduit
- Indoor or outdoor use (lay-in lug)
- Use with locknut to terminate service conduit to a cabinet
- Lug provided for bonding jumper to a neutral bus bar
- Round surface of bushing prevents damage to wire insulation
- Plastic liner prevents damage to wire insulation

Standard Material

- Body - Zinc die cast
- Plastic insulator
- Lug - Aluminum
- Clamping screw - Steel
- Set screws - Steel



E195122



Catalog Number	UPC	Size	Grounding Lug Wire Size		Unit Carton	Ship Case	Weight/Case	Inches	
			Min.	Max.				A	B
331	13130	1/2"	14	4	50	500	30	1.04	.38
332	13140	3/4"	14	4	50	500	35	1.26	.41
333	13150	1"	14	4	25	250	23	1.53	.50
334	13160	1-1/4"	14	4	20	200	26	1.86	.53
334A	13170	1-1/4"	14	1/0	20	200	26	1.86	.53
335	13180	1-1/2"	14	4	10	100	16	2.13	.56
335A	13190	1-1/2"	14	1/0	10	100	16	2.13	.56
336	13200	2"	14	4	10	100	21	2.60	.66
336A	13210	2"	14	1/0	10	100	21	2.60	.66
337	13220	2-1/2"	14	1/0	---	50	20	3.15	.75
337A	13230	2-1/2"	6	250 MCM	---	50	20	3.15	.75
338	13240	3"	14	1/0	---	50	29	3.76	.75
338A	13250	3"	6	250 MCM	---	50	29	3.76	.75
339	13260	3-1/2"	14	1/0	---	10	15	4.27	.75
339A	13270	3-1/2"	6	250 MCM	---	10	15	4.27	.75
340	13280	4"	14	1/0	---	10	20	4.76	.75
340A	13290	4"	6	250 MCM	---	10	20	4.76	.75