

Insulated Metallic Grounding Bushings

With Aluminum Lay-In Lug - Threadless Set Screw Type

Malleable Iron

Features

- Liner is rated flame retardant to 105°C
- Set-screws allowing the fitting to lock bushing in any desired position
- For use on threaded or threadless Rigid conduit or IMC

Applications

- Indoor or outdoor use (lay-in lug)
- Use with locknut to terminate service conduit to a cabinet
- Lug provided for bonding jumper to a neutral bus bar
- Round surface of bushing prevents damage to wire insulation
- Plastic liner prevents damage to wire insulation

Standard Material


- Body - Malleable iron
- Plastic insulator
- Lug - Aluminum
- Clamping screw - Steel
- Set screws - Steel

Standard Finish

- Body - Zinc plated



E195122



Catalog Number	UPC	Size	Grounding Lug Wire Size		Unit Carton	Ship Case	Weight/Case	Inches	
			Min.	Max.				A	B
331MSS	13321	1/2"	14	4	50	500	25	1.08	.57
332MSS	13331	3/4"	14	4	50	500	30	1.31	.57
333MSS	13341	1"	14	4	25	250	23	1.61	.65
334MSS	13351	1-1/4"	14	4	20	200	30	1.91	.71
335MSS	13361	1-1/2"	14	4	10	100	25	2.16	.73
336MSS	13371	2"	14	4	10	100	30	2.72	.73
337MSS	13391	2-1/2"	14	1/0	5	50	38	3.23	.94
338MSS	13411	3"	14	1/0	---	25	35	3.88	.94
339MSS	13431	3-1/2"	14	1/0	---	10	15	4.43	.94
340MSS	13451	4"	14	1/0	---	10	20	4.89	.94
340AMSS	13461	5"	6	250 MCM	---	10	25	6.10	1.14
340BMSS	13471	6"	6	250 MCM	---	10	35	7.15	1.14