

Straight Liquidtight Connectors

Steel

Features

- Industrial specification grade, screw machined steel
- UL listed liquidtight flexible metal conduit fittings are suitable for use in the following hazardous locations under: NEC 501-4(b), 502-4(a), (2)503-3(a) Class 1 Div. 2, Class II Div. 1 and 2, Class III Div. 1 and 2 are suitable for grounding in sizes 3/8" through 1-1/2" under NEC 351-1
- Includes sealing washer
- Corrosion resistant protection from moisture & oils
- Designed to protect against excessive vibration

Applications


- Bonds liquidtight conduit to box or enclosure
- Straight type

Standard Material

- Steel

Standard Finish

- Zinc plated



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight Case	Inches		
						A	B	C
470ST	14439	3/8" 1/2" KO	20	200	26	1.09	1.19	.63
471ST	14441	1/2"	20	200	26	1.19	1.34	.63
472ST	14451	3/4"	10	100	18	1.43	1.43	.63
473ST	14461	1"	5	50	16	1.75	1.63	.66
474ST	14471	1-1/4"	5	50	37	2.16	1.84	.67
475ST	14481	1-1/2"	2	20	21	2.38	2.00	.72
476ST	14491	2"	2	20	3	2.88	2.13	.72