

# Rigid Straps

## Snap-On Type - Two Hole - Steel

### Features

- Greater load bearing capability
- Easy to install

### Applications


- Indoor or outdoor use
- Use to secure EMT, Rigid or IMC conduit to wood, masonry or where greater load bearing is required

### Standard Material

- Steel

### Standard Finish

- Zinc plated



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches	
						A	B
<b>541A</b>	15043	<b>1/4"</b>	100	1000	18	2.15	.562
<b>541B</b>	15046	<b>3/8"</b>	100	1000	18	2.20	.562
<b>541</b>	15150	<b>1/2"</b>	50	500	13	2.43	.625
<b>542</b>	15160	<b>3/4"</b>	50	500	16	2.81	.685
<b>543</b>	15170	<b>1"</b>	25	250	12	3.28	.750
<b>544</b>	15180	<b>1-1/4"</b>	20	200	13	4.02	.875
<b>545</b>	15190	<b>1-1/2"</b>	10	100	12	4.58	1.00
<b>546</b>	15200	<b>2"</b>	---	50	7	5.22	1.00
<b>527*</b>	15010	<b>2-1/2"</b>	---	25	6	5.91	1.00
<b>528*</b>	15020	<b>3"</b>	---	25	7	6.71	1.00
<b>529*</b>	15030	<b>3-1/2"</b>	---	25	8	7.51	1.00
<b>530*</b>	15040	<b>4"</b>	---	25	7	8.31	1.00
<b>530A</b>	15042	<b>5"</b>	---	10	5	10.60	1.25
<b>530B</b>	15044	<b>6"</b>	---	10	6	11.85	1.25

\*EMT and Rigid