

# Rigid Straps

## Snap-On Type - One Hole - Hot Dip Galvanized

### Features

- Hot dip galvanized for added durability and corrosion protection

### Applications

- Use to secure Rigid or IMC conduit to wood, masonry or where greater load bearing is required

### Standard Material

- Malleable iron


### Standard Finish

- Hot dip galvanized



E174011

Conforms to finish thickness ASTM A123/123M  
UL 2239  
NEMA FB 1  
Federal Spec. A-A-50553



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	A	Inches B	C
<b>561HDG</b>	86589	<b>1/2"</b>	100	1000	40	1.98	.67	.97
<b>562HDG</b>	86590	<b>3/4"</b>	50	500	25	2.37	.76	1.10
<b>563HDG</b>	86591	<b>1"</b>	25	250	20	2.90	.82	1.44
<b>564HDG</b>	86592	<b>1-1/4"</b>	20	250	25	3.12	.82	1.77
<b>565HDG</b>	86593	<b>1-1/2"</b>	10	200	32	3.90	1.05	2.06
<b>566HDG</b>	86594	<b>2"</b>	---	100	36	4.77	1.36	2.59
<b>567HDG</b>	86595	<b>2-1/2"</b>	---	25	17	5.45	1.36	3.05
<b>568HDG</b>	86596	<b>3"</b>	---	25	25	6.74	1.54	3.77
<b>569HDG</b>	86597	<b>3-1/2"</b>	---	25	38	7.72	1.91	4.24
<b>570HDG</b>	86598	<b>4"</b>	---	10	23	8.13	2.07	4.98
<b>570AHDG</b>	86599	<b>5"</b>	---	10	34	10.94	2.55	6.22
<b>570BHDG</b>	86600	<b>6"</b>	---	10	40	12.71	2.91	7.45