

Job Name/Title: \_\_\_\_\_ Catalog Number \_\_\_\_\_  
 Contractor: \_\_\_\_\_ Notes: \_\_\_\_\_

# Rigid Couplings

## Tubular Threaded Type - Galvanized Steel

### Features

- NPSM thread type

### Application

- Indoor or outdoor use
- Use to join and ensure proper alignment of threaded Rigid or IMC conduit

### Standard Material


- Steel

### Standard Finish

- Zinc plated



1/2"-4" meet UL 6 and ANSI C80.1  
Federal Specification WW-C-563



Catalog Number	UPC	Size	Threads Per Inch	Ship Case	Weight/Case	Inches	
						A	B
51	10130	1/2"	14	150	14	1.63	1.563
52	87230	3/4"	14	50	10	1.64	1.625
53	10150	1"	11-1/2	30	9	1.97	2
54	10160	1-1/4"	11-1/2	25	10	2.03	2.063
55	10170	1-1/2"	11-1/2	25	14	2.06	2.063
56	10180	2"	11-1/2	20	12	2.13	2.125
57	10190	2-1/2"	8	12	24	2.19	3.125
58	10200	3"	8	8	18	3.31	3.25
59	10210	3-1/2"	8	4	15	3.41	3.375
60	10220	4"	8	4	13	3.52	3.50
60A	10230	5"	8	2	11	3.95	3.75
60B	10240	6"	8	3	12	4.25	4