

# Top-Bite Saddle Type Connectors

## With Insulated Throat

### Features

- Dual gripping saddle clamps
- Saddle clamps ride up and down on screw for ease of installation
- Tri combo head screw

### Applications



- To connect Flex, AC, and MC cables to a box or enclosure

### Standard Material

- Tubular steel
- Steel locknuts

### Standard Finish

- Zinc plated



Catalog Number	UPC	Size	KO	Unit Carton	Ship Case	Weight/Case	Inches		
							A	B	C
<b>630TBS*</b>	85172	<b>3/8"</b>	1/2"	25	100	10	1.188	1.25	.50
<b>631TBS*</b>	85173	<b>1/2"</b>	1/2"	25	100	15	1.375	1.25	.438
<b>632TBS*</b>	85174	<b>3/4"</b>	3/4"	10	50	9	1.375	1.438	.438
<b>633TBS*</b>	85175	<b>1"</b>	1"	5	25	9	1.563	1.813	.50
<b>634TBS</b>	85176	<b>1-1/4"</b>	1-1/4"	5	25	14	2.188	2.125	.625
<b>635TBS</b>	85177	<b>1-1/2"</b>	1-1/2"	2	10	8	2.438	2.50	.625
<b>636TBS</b>	85178	<b>2"</b>	2"	---	5	5	2.563	3	.625
<b>637TBS</b>	85179	<b>2-1/2"</b>	2-1/2"	---	4	6	2.688	3.625	.813
<b>638TBS</b>	85180	<b>3"</b>	3"	---	5	11	2.813	4.25	.938
<b>639TBS</b>	85181	<b>3-1/2"</b>	3-1/2"	---	1	3	2.938	4.75	1
<b>640TBS</b>	85182	<b>4"</b>	4"	---	1	3	3	5.813	1.031

\*UL listed for MCAP/MCI-A & MCI-A HCF cables