

# EMT Couplings

## Compression Type - Steel

### Features

- Compression type couplings
- Concrete tight
- Assembled with a steel locknut

### Applications

- Use to join two lengths of EMT

### Standard Material

- Steel


### Standard Finish

- Zinc plated



E18472

UL Standard: 514B  
Fed. Spec. W-F-408E  
NEMA: FB 1



Catalog Number	UPC	Size	Unit Carton	Ship Case	Weight/Case	Inches	
						A	B
<b>661S</b>	17010	<b>1/2"</b>	25	250	32	1.688	1.250
<b>662S</b>	17020	<b>3/4"</b>	25	250	40	2.000	1.563
<b>663S</b>	17030	<b>1"</b>	10	100	31	2.125	1.813
<b>664S</b>	17040	<b>1-1/4"</b>	---	25	15	3.063	2.188
<b>665S</b>	17050	<b>1-1/2"</b>	---	20	15	3.125	2.438
<b>666S</b>	17060	<b>2"</b>	---	15	18	3.375	2.938
<b>667S</b>	17061	<b>2-1/2"</b>	---	6	14	4.875	3.688
<b>668S</b>	17062	<b>3"</b>	---	6	19	5.250	4.313
<b>669S</b>	17063	<b>3-1/2"</b>	---	6	21	5.500	4.875
<b>670S</b>	17064	<b>4"</b>	---	3	15	5.750	5.375