

Sealing Locknuts

Steel

Features

- Zinc plated with PVC molded gasket for a watertight seal

Applications


- Indoor or outdoor use
- Use to secure Rigid, IMC conduit or various threaded fittings to a steel outlet box or other metal enclosures, when moisture proof protection is required

Standard Material

- Steel

Standard Finish

- Zinc plated
- PVC gasket



Catalog Number	UPC	Size	Threads Per Inch	Unit Carton	Ship Case	Weight/Case	Inches		
							A	B	Thread Pitch Diameter
711	17450	1/2"	14	50	500	10	1.12	.26	.787-.797
712	17460	3/4"	14	50	500	16	1.37	.27	.999-1.009
713	17470	1"	11-1/2	25	250	4	1.75	.28	1.250-1.260
714	17480	1-1/4"	11-1/2	10	100	8	2.06	.32	1.595-1.605
715	17490	1-1/2"	11-1/2	10	100	8	2.37	.32	1.837-1.847
716	17500	2"	11-1/2	10	100	12	2.87	.32	2.307-2.317
717	17510	2-1/2"	8	---	25	5	3.43	.32	2.777-2.788
718	17520	3"	8	---	25	5	4.12	.32	3.403-3.414
719	17530	3-1/2"	8	---	25	6	4.62	.32	3.892-3.904
720	17540	4"	8	---	25	6	5.18	.32	4.399-4.411
720A	85017	5"	8	---	5	6	6.67	.50	5.488-5.500
720B	17542	6"	8	---	5	10	7.83	.52	6.545-6.557