

Solderless Lugs

Single Hole - Offset Tang - Copper

Features


- Unique pressure bar provides solid grip between conductor and terminal
- Hole for offset tang mounting

Applications

- Terminates an electrical conductor to facilitate mechanical connection

Standard Material

- Copper
- Steel screw



Catalog Number	UPC	Amp Rating	Recommended Torque in Lbs.	Bolt Size	Ship Case	Weight/Case	Wire Range Min. - Max.	Inches			
								A	B	C	D
820	18270	25	20	1/8"	250	3	#14-#10	1.00	.3125	.6875	.125
821	18280	35-50	45	3/16"	250	6	#14-#6	1.1875	.375	.75	.1875
822	18290	70	50	1/4"	200	6	#14-#4	1.3125	.50	.8125	.25
823	18300	70-90	50	1/4"	200	9	#12-#2	1.5313	.50	1.00	.25
824	18310	125	50	1/4"	100	11	#8-1/0	1.9688	.625	1.375	.25
825	18320	175	124	3/8"	25	3	#4-3/0	2.1875	.75	1.5625	.375
826	18330	225	204	5/16"	25	6	#6-4/0	2.625	1.00	2.00	.3125
827	18340	300	325	3/8"	20	10	1/0- 350 MCM	3.1875	1.00	2.625	.375
828	18350	400	375	3/8"	10	7	4/0-500 MCM	4.25	1.50	2.75	.375
829	18360	650	500	1/2"	4	7	600 MCM-100 MCM	4.625	2.00	3.6875	.50