

Flexible Cord Connectors

Strain Relief - Zinc Die Cast

Features


- Provides excellent strain relief for indoor and outdoor use
- Prevents cable pullout
- Provides tight seal against elemental damage

Application

- Indoor or outdoor use

Standard Material

- Zinc die cast



Catalog Number	UPC	Size	Cable Range	Unit Carton	Ship Case	Weight/Case	Inches		Range	
							A	B	Min.	Max.
881	18880	1/2"	.190 - .260	25	250	43	.96	1.30	.190	.260
881A	18890	1/2"	.260 - .375	25	250	43	.96	1.30	.260	.375
881B	18900	1/2"	.375 - .500	25	250	43	.96	1.30	.375	.500
882	18910	3/4"	.375 - .500	25	250	65	1.20	1.32	.440	.500
882A	18920	3/4"	.500 - .625	25	250	65	1.20	1.32	.500	.625
882B	18930	3/4"	.625 - .750	25	250	65	1.20	1.32	.625	.725
883	18939	1"	.375 - .500	10	100	34	1.51	1.58	.375	.500
883A	18940	1"	.500 - .625	10	100	34	1.51	1.58	.500	.625
883B	18950	1"	.625 - .750	10	100	34	1.51	1.58	.625	.750
883C	18960	1"	.750 - .880	10	100	34	1.51	1.58	.750	.880
883D	18970	1"	.880 - .985	10	100	34	1.51	1.58	.875	.985