

AC Whips Non-Metallic

Features

- Liquidtight
- 240 Volt
- Single phase A/C seal proof power whip
- Assembled with all UL components
- Available in 1/2" and 3/4" conduit size
- 4' and 6' lengths, designed for easy installation
- Resists corrosion, oil, water, outdoor, and sunlight damage



Applications

- Connection between outside air conditioning unit and electrical power source; typically used to connect compressor to AC disconnect box

Standard Material

- Non-metallic

Catalog Number	UPC	Connectors	Conduit Size	Wire Type	Wires	Ship Case	Weight/Case	Length in Feet	Wire Size	Reducing Washer
ACW10	33782	1/2" ST. 1/2" 90°	1/2"	#10 Gauge Stranded THNN	1-Black, 1-Red, 1-Green	12	400	4	#10	1/2" x 3/4"
ACW11	33783	1/2" ST. 1/2" 90°	1/2"	#10 Gauge Stranded THNN	1-Black, 1-Red, 1-Green	12	400	6	#10	1/2" x 3/4"
ACW12	33778	3/4" ST. 3/4" 90°	3/4"	#8 Gauge Stranded THNN	1-Black, 1-Red, 1-Green	12	400	4	#8	3/4" x 1"
ACW13	33779	3/4" ST. 3/4" 90°	3/4"	#8 Gauge Stranded THNN	1-Black, 1-Red, 1-Green	12	400	6	#8	3/4" x 1"
ACW1412	85015	1/2" ST. 1/2" 90°	1/2"	#12 Solid	2-Black, 1-Green	24	17	4	#12	1/2" x 3/4"
ACW1612	85014	1/2" ST. 1/2" 90°	1/2"	#12 Solid	2-Black, 1-Green	24	13	6	#12	1/2" x 3/4"
ACW16124W	85016	1/2" ST. 1/2" 90°	1/2"	#12 Solid 4 Wire	1-Black, 1-Red, 1-Green, 1-White	24	13	6	#12	1/2" x 3/4"

All AC Whips include conduit, I-NM straight and I-NM 90° fitting and reducing washer.
All wire leads are 1 foot lead wire length at each end.