

# Rigid Conduit Bodies

## Threaded C Type

### Features

- Threaded C type
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

### Applications


- Provides access to conductors for pulling, splicing and maintenance

### Standard Material

- Copper free aluminum die cast

### Standard Finish

- Powder coat



Catalog Number	UPC	Size	Max. Number	Wire Size		Unit Carton	Ship Case	Weight/Case	Inches		
				Max. Size					A	B	C
<b>C1</b>	19900	1/2"	1	6 AWG		10	100	24	4.720	1.370	1.330
<b>C2</b>	19910	3/4"	2	6 AWG		10	50	21	5.570	1.625	1.540
<b>C3</b>	19920	1"	3	6 AWG		5	25	15	6.460	1.900	1.740
<b>C4</b>	19930	1-1/4"	3	2 AWG		2	10	15	8.528	2.770	2.490
<b>C5</b>	19940	1-1/2"	3	2 AWG		2	10	17	8.528	2.770	2.490
<b>C6</b>	19950	2"	3	2/O AWG		5	5	13	10.831	3.335	3.100
<b>C7</b>	19960	2-1/2"	3	4/O AWG		---	1	6	13.500	4.060	4.450
<b>C8</b>	19970	3"	3	250 MCM		---	1	6	13.000	4.685	4.450
<b>C9</b>	19980	3-1/2"	3	350 MCM		---	1	8	15.937	5.450	5.500
<b>C10</b>	19990	4"	4	350 MCM		---	1	8	15.937	5.450	5.500