

# EMT and Rigid Combination Conduit Bodies

## C Type

### Features

- Combination C type
- NPT tapered hubs
- Suitable for use in concrete
- NEMA FB 1 rated for wet locations use with threaded rigid metal conduit only

### Applications


- Provides access to conductors for pulling, splicing and maintenance

### Standard Material

- Copper free aluminum die cast
- Steel screws

### Standard Finish

- Powder coat



Catalog Number	UPC	Size	Max. Number	Max. Size	Unit Carton	Ship Case	Weight/Case	Inches		
								A	B	C
<b>C1SS</b>	19902	<b>1/2"</b>	1	6 AWG	10	100	24	5.35	1.31	1.31
<b>C2SS</b>	19912	<b>3/4"</b>	2	6 AWG	10	50	21	6.00	1.62	1.48
<b>C3SS</b>	19922	<b>1"</b>	3	6 AWG	5	25	15	7.06	1.88	1.75
<b>C4SS</b>	19932	<b>1-1/4"</b>	3	2 AWG	2	10	15	9.25	2.50	2.40
<b>C5SS</b>	19942	<b>1-1/2"</b>	3	2 AWG	2	10	17	9.25	2.67	2.40
<b>C6SS</b>	19952	<b>2"</b>	3	2/0 AWG	---	5	13	11.50	3.29	3.05