

Top-Flex II Tubing

Non-Metallic



Features

- Resists corrosion, abrasion, oil, water, acid, metal shavings, and rough environments
- UL Type B flexible non-metallic liquidtight conduit

Applications

- Indoor or outdoor use

Standard Material

- Integral Rigid and flexible PVC construction



Catalog Number	UPC	Size	Ship Case	Weight/Case	Outside Diameter		Inside Diameter		Wall thickness
					Min.	Max.	Min.	Max.	
HF214	30065	1/4"	100'	4	.560	.575	.385	.405	.17
HF238	30070	3/8"	100'	6	.690	.710	.484	.504	.21
HF212	30080	1/2"	100'	8	.820	.840	.622	.642	.21
HF234	30090	3/4"	100'	10	1.030	1.050	.820	.840	.21
HF21	30100	1"	100'	15	1.290	1.315	1.041	1.066	.25
HF2114	23412	1-1/4"	100'	19	1.630	1.660	1.380	1.410	.25
HF2112	23415	1-1/2"	50'	22	1.865	1.900	1.575	1.600	.30
HF22	23416	2"	50'	60	2.340	2.375	2.020	2.045	.33

UL TYPE B FLEXIBLE NONMETALLIC LIQUIDTIGHT CONDUIT

- 1/4" through 1" trade sizes, consult Topaz for 1-1/4", 1-1/2", and 2" sizes
- Use with top-flex nylon connectors- straight or right angle
- Resists, oil and water
- Maximum flexibility, can be used in extremely tight quarters
- Smooth inside for easier wire pulling
- Lightweight and lower installed cost
- Quick installation, cuts with utility knife or PVC cutter (CATALOG #VF28)
- Integral Rigid and flexible PVC construction
- Ideal for fiberoptic cable protection
- Suitable for use in high vibration or flexible applications:
 - automotive equipment
 - computers and peripherals
 - fiber optics lab equipment
 - lasers
 - office equipment
 - processing controls and monitoring equipment
 - robotics
- 70° C