

Rigid Conduit Bodies

Threaded LB Type - Malleable Iron

Features

- NPT tapered hubs
- Suitable for use in concrete

Applications


- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Malleable iron

Standard Finish

- Zinc plated, aluminum enameled



Catalog Number	UPC	Size	Wire Size		Ship Case	Weight/Case	Inches		
			Max. Number	Max. Size			A	B	C
LB1M	20940	1/2"	---	---	10	7	4.56	2.06	1.31
LB2M	20950	3/4"	3	6 AWG	10	9	5.31	2.37	1.48
LB3M	20960	1"	3	4 AWG	5	6	6.25	2.63	1.75
LB4M	20970	1-1/4"	3	2 AWG	5	23	8.22	3.50	2.40
LB5M	20980	1-1/2"	3	1/0 AWG	10	26	8.22	3.75	2.40
LB6M	20990	2"	3	4/0 AWG	5	26	10.48	4.31	3.05
LB7M	21000	2-1/2"	3	300 MCM	1	10	13.75	4.45	4.38
LB8M	21010	3"	3	350 MCM	1	13	13.75	4.45	4.38
LB9M	21020	3-1/2"	3	500 MCM	1	22	16.75	5.80	5.63
LB10M	21030	4"	3	500 MCM	1	24	16.75	5.80	5.63