

# Rigid Conduit Bodies

## Threaded LB Type - Hot Dip Galvanized

### Features

- Hot dip galvanized finish provides superior protection against severe environmental factors

### Applications

- Provides taps for branch conduit runs
- Enables 90 degree bends in conduit runs

### Standard Material


- Malleable iron

### Standard Finish

- Hot dip galvanized



Conforms to finish thickness ASTM  
A123/123M  
UL 514A and UL 514D  
NEMA FB 1  
Federal Spec. A-A-50563



Catalog Number	UPC	Size	Wire Size		Internal Volume (in <sup>3</sup> )	Ship Case	Weight/Case	Inches		
			Max. Number	Max. Size				A	B	C
<b>LB1MHDG</b>	86613	<b>1/2"</b>	---	---	4.5	10	7	4.69	2.18	1.36
<b>LB2MHDG</b>	86614	<b>3/4"</b>	3	6 AWG	7.5	10	9	5.42	2.36	1.57
<b>LB3MHDG</b>	86615	<b>1"</b>	3	4 AWG	12.5	5	6	6.28	2.86	1.79
<b>LB4MHDG</b>	86616	<b>1-1/4"</b>	3	2 AWG	32.3	5	12	8.12	3.49	2.52
<b>LB5MHDG</b>	86617	<b>1-1/2"</b>	3	1/0 AWG	35.3	2	11	8.15	3.69	2.52
<b>LB6MHDG</b>	86618	<b>2"</b>	3	4/0 AWG	73	1	6	10.53	4.52	3.15
<b>LB7MHDG</b>	86619	<b>2-1/2"</b>	3	300 MCM	142	1	10	13.76	5.39	4.45
<b>LB8MHDG</b>	86620	<b>3"</b>	3	400 MCM	173	1	13	13.82	6.18	4.45
<b>LB9MHDG</b>	86621	<b>3-1/2"</b>	3	500 MCM	300	1	22	16.65	7.19	5.53
<b>LB10MHDG</b>	86622	<b>4"</b>	3	500 MCM	328	1	24	16.65	7.36	5.53