

EMT and Rigid Combination Conduit Bodies with Covers and Gaskets

LL Type

Features

- Combination LL type with cover and gasket
- NPT tapered hubs
- Suitable for use in concrete
- NEMA FB 1 rated for wet locations use with threaded rigid metal conduit only

Applications

- Provides access to conductors for pulling, splicing and maintenance

Standard Material


- Copper free aluminum die cast
- Cover - Stamped steel
- Gasket - Neoprene rubber

Standard Finish

- Powder coat



E195124
NEMA FB 1



Catalog Number	UPC	Size	Max. Number	Max. Size	Unit Carton	Ship Case	Weight/Case	A	Inches B	C
LL1SSCG	83774	1/2"	1	6 AWG	10	100	36	4.56	1.31	2.06
LL2SSCG	83775	3/4"	2	6 AWG	10	50	23	5.31	1.62	2.23
LL3SSCG	83776	1"	3	6 AWG	5	25	19	6.25	1.88	2.50
LL4SSCG	83777	1-1/4"	3	2 AWG	2	10	15	8.22	2.50	3.40
LL5SSCG	83778	1-1/2"	3	2 AWG	2	10	16	8.22	2.67	3.48
LL6SSCG	83779	2"	3	2/0 AWG	---	5	14	10.48	3.29	4.07