

# Rigid Conduit Bodies

## Threaded LR Type - Hot Dip Galvanized

### Features

- Hot dip galvanized finish provides superior protection against severe environmental factors

### Applications

- Provides taps for branch conduit runs
- Enables 90 degree bends in conduit runs

### Standard Material


- Malleable iron

### Standard Finish

- Hot dip galvanized



Conforms to finish thickness ASTM  
A123/123M  
UL 514A and UL 514D  
NEMA FB 1  
Federal Spec. A-A-50563



Catalog Number	UPC	Size	Wire Size		Internal Volume (in <sup>3</sup> )	Ship Case	Weight/Case	Inches		
			Max. Number	Max. Size				A	B	C
<b>LR1MHDG</b>	86633	<b>1/2"</b>	---	---	4.5	10	7	4.69	1.46	2.08
<b>LR2MHDG</b>	86634	<b>3/4"</b>	3	6 AWG	7.5	10	10	5.42	1.65	2.31
<b>LR3MHDG</b>	86635	<b>1"</b>	3	4 AWG	12.5	5	6	6.28	1.98	2.68
<b>LR4MHDG</b>	86636	<b>1-1/4"</b>	3	2 AWG	32.3	5	13	8.12	2.60	3.41
<b>LR5MHDG</b>	86637	<b>1-1/2"</b>	3	1/0 AWG	35.3	2	6	8.15	2.80	3.45
<b>LR6MHDG</b>	86638	<b>2"</b>	3	4/0 AWG	73	1	6	10.53	3.52	4.15
<b>LR7MHDG</b>	86639	<b>2-1/2"</b>	3	300 MCM	142	1	10	13.76	3.98	5.86
<b>LR8MHDG</b>	86640	<b>3"</b>	3	350 MCM	173	1	13	13.82	4.65	5.92
<b>LR9MHDG</b>	86641	<b>3-1/2"</b>	3	350 MCM	300	1	22	16.65	5.43	7.14
<b>LR10MHDG</b>	86642	<b>4"</b>	3	350 MCM	330	1	24	16.65	5.74	7.19