

Rigid Conduit Bodies

Threaded LR Type

Features

- Threaded LR type
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications


- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast

Standard Finish

- Powder coat



Catalog Number	UPC	Size	Max. Number	Wire Size		Unit Carton	Ship Case	Weight/Case	Inches		
				Max. Size					A	B	C
LR1	21240	1/2"	1	6 AWG		10	100	29	4.295	1.370	2.030
LR2	21250	3/4"	2	6 AWG		10	50	24	5.090	1.625	2.330
LR3	21260	1"	3	6 AWG		5	25	19	5.915	1.900	2.650
LR4	21270	1-1/4"	3	2 AWG		2	10	14	7.894	2.770	3.385
LR5	21280	1-1/2"	3	2 AWG		2	10	17	7.894	2.770	3.385
LR6	21290	2"	3	2/0 AWG		1	5	14	10.134	3.335	3.810
LR7	21300	2-1/2"	3	4/0 AWG		---	1	6	13.500	4.063	5.709
LR8	21310	3"	3	250 MCM		---	1	6	12.750	4.682	5.506
LR9	21320	3-1/2"	3	350 MCM		---	1	8	15.500	5.452	6.171
LR10	21330	4"	4	350 MCM		---	1	8	15.500	5.452	6.171