

Knockout Bushings

6/6 Nylon

Features

- Suitable for use with electrical knockouts

Application

- For use in mounting panels up to 1/4" thick, convert raw edged holes to smooth, neat, insulated holes
- Insulate and mechanically protect electrical and telecommunications cables, tubing, hose, rope and utility lines
- Locking fingers snap into holes with fingertip pressure; capable of withstanding a push back force of greater than 35 pounds



Standard Material

- 6/6 nylon

| Catalog Number | UPC | Inside Diameter | KO Size | Unit Carton | Ship Case | Weight/Case |
|-----------------|-------|-----------------|---------|-------------|-----------|-------------|
| SB8756 | 32620 | 3/8" | 1/2" | 100 | 1000 | 4 |
| SB8757 | 32630 | 7/16" | 1/2" | 100 | 1000 | 4 |
| SB8758 | 32640 | 1/2" | 1/2" | 100 | 1000 | 4 |
| SB8759 | 32650 | 9/16" | 1/2" | 100 | 1000 | 4 |
| SB87510 | 32660 | 5/8" | 1/2" | 100 | 1000 | 4 |
| SB87511 | 32670 | 11/16" | 1/2" | 100 | 1000 | 4 |
| SB109313 | 32690 | 13/16" | 3/4" | 100 | 1000 | 6 |
| SB109314 | 32700 | 7/8" | 3/4" | 100 | 1000 | 6 |
| SB109315 | 32710 | 15/16" | 3/4" | 100 | 1000 | 6 |
| SB137514 | 32760 | 7/8" | 1" | 100 | 1000 | 8 |
| SB137516 | 32770 | 1" | 1" | 100 | 1000 | 8 |
| SB175022 | 32810 | 1-3/8" | 1-1/4" | 50 | 500 | 6 |
| SB200026 | 32820 | 1-5/8" | 1-1/2" | 50 | 500 | 7 |
| SB2.531 | 32840 | 1-31/32" | 2" | 10 | 100 | 4 |
| SB3.039 | 32850 | 2-15/32" | 2-1/2" | 10 | 100 | 4 |
| SB3.547 | 32860 | 2-15/16" | 3" | 10 | 100 | 4 |
| SB4.055 | 32870 | 3-7/16" | 3-1/2" | 10 | 100 | 4 |