

Rigid Conduit Bodies with Cover and Gasket

Threaded T Type

Features

- Threaded T type with cover and gasket
- NPT tapered hubs
- Suitable for use in concrete
- Suitable for use in wet locations

Applications


- Provides access to conductors for pulling, splicing and maintenance

Standard Material

- Copper free aluminum die cast
- Cover - Stamped steel
- Gasket- Neoprene rubber

Standard Finish

- Powder coat



Catalog Number	UPC	Size	Wire Size		Unit Carton	Ship Case	Weight/ Case	Inches		
			Max. Number	Max. Size				A	B	C
T1CG	21731	1/2"	1	6 AWG	10	100	38	4.720	1.370	1.330
T2CG	21741	3/4"	2	6 AWG	10	50	30	5.570	1.625	1.540
T3CG	21751	1"	3	6 AWG	5	25	20	6.460	1.900	1.740
T4CG	21761	1-1/4"	3	2 AWG	2	10	19	8.528	2.770	2.490
T5CG	21771	1-1/2"	3	2 AWG	2	10	21	8.528	2.770	2.490
T6CG	21781	2"	3	2/O AWG	---	5	5	10.831	3.335	3.100
T7CG	21791	2-1/2"	3	4/O AWG	---	1	8	13.500	4.060	5.825
T8CG	21801	3"	3	250 MCM	---	1	8	13.500	4.685	5.825
T9CG	21811	3-1/2"	3	350 MCM	---	1	11	15.937	5.450	7.060
T10CG	21821	4"	4	350 MCM	---	1	11	15.937	5.450	7.060