

Wire Connectors

Winged



Features

- Easy installation
- Flame retardant; temperature rating of 105° C
- Color coded for easy size and capacity identification
- Square wire spring insert for secure connections

Applications

- Positive grip design is ideal for insulating two or more conductors
- Reusable for easy circuit changes

Standard Material

- Polypropylene

Catalog Number	UPC	Color	Unit Carton	Ship Case	Weight/Case	Wire Range		Volts
						Min.	Max.	
Joins #18 through #10 AWG								
WY1	21930	Yellow	100/Box	5000	16	2#18	3#12	600V
WY2	21940	Yellow	500/Bag	5000	16	2#18	3#12	600V
Joins #18 through #10 AWG								
WR1	21950	Red	100/Box	5000	27	2#14	5#12	600V
WR2	21960	Red	500/Bag	5000	27	2#14	5#12	600V
Joins #14 through #6 AWG								
WB1	21970	Blue	50/Box	500	13	3#12	1#6 & 2#8	600V
WB2	21980	Blue	250/Bag	1000	13	3#12	1#6 & 2#8	600V
Joins #14 through #10 AWG								
WG1	21993	Green	100/Box	5000	16	2#14	5#12	600V
WG2	21990	Green	500/Bag	5000	16	2#14	5#12	600V
Joins #22 through #8 AWG								
WT1	21992	Tan	100/Box	1000	13	3#22	3#10	600V
WT2	21991	Tan	500/Bag	1000	35	3#22	3#10	600V