

Product Description

POWERply® Standard Smooth is a smooth surfaced, modified bitumen sheet used in conjunction with recommended waterproofing membranes as an extremely heavy-duty protection course, primarily in horizontal applications.

Basic Uses

POWERply Standard Smooth sheeting is used as a strong protection course for Tremco hot applied waterproofing membranes.

Availability

Immediately available from your local Tremco Sales Representative, Tremco Distributor or Tremco Warehouse.

Packaging

3' x 56' 8" (0.91 M x 17.3 M) / roll

Limitations

- Not to be exposed to solvents, oils, or other contaminants harmful to asphaltic materials.
- Not intended for use with Tremco TREMproof® 201/60 or Tremco TREMproof 250GC cold fluid-applied waterproofing membranes.
- Not intended for UV exposure.

Installation

Immediately install POWERply Standard Smooth over the TREMproof 6100 while membrane is still warm and tacky. Adjacent sheets should be overlapped a minimum of 2" (51 mm).

Warranty

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of Tremco Product proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TYPICAL PHYSICAL PROPERTIES

PROPERTY	VALUES US	VALUES SI
Composition	SBS Bitumen Modified	
Thickness	80 mils (2 mm)	2 mm
Puncture Resistance	70 lb	
Weight	105 lb /roll	47.6 kg/roll
Dimension	3' x 56' 8" / roll, 170 ft ² / roll	0.91 M x 17.3 M/roll, 15.7 M ² /roll

0918/POWERSSDS-BG

Tremco Commercial Sealants & Waterproofing

3735 Green Rd
Beachwood OH 44122
216.292.5000 / 800.321.7906

1451 Jacobson Ave
Ashland OH 44805
419.289.2050 / 800.321.6357

220 Wicksteed Ave
Toronto ON M4H1G7
416.421.3300 / 800.363.3213

1445 Rue de Coulomb
Boucherville QC J4B 7L8
514.521.9555

