

TREMprime Multi-Surface Urethane Primer

Urethane Tie-In Primer

Product Description

TREMprime Multi-Surface Urethane Primer is a two-component, quick-drying, epoxy-based, VOC-compliant primer primarily for use with Vulkem® urethane deck coating and liquid-applied waterproofing products. It may also be used with Vulkem and Tremco branded urethane sealants.

Basic Uses

Porous surfaces, interlaminary, urethane coatings. Low-VOC (<60 g/L), two-part epoxy primer used to condition and prep porous surfaces and existing coatings for application of a new coating layer. Apply with a short nap roller or brush evenly to the surface. Primer must dry completely before coating application as indicated by turning from milky-white to completely clear.

Features & Benefits

- Improves wear and chemical resistance
- Reduces water and salt absorption
- Water-based, low odor
- Resistant to mild acids
- Can be used as a primer under epoxy or urethane coatings
- Resistant to gasoline and other solvent spills

Coverage Rate

Approximately 200 – 300 ft²/gal

Packaging

3-gal (11.4- L) kits:

Part A: 2 gal (7.6 L) can

Part B: 1 gal (3.8 L) can

Availability

Immediately available from your local Tremco Sales Representative, Tremco Distributor or Tremco Warehouse.

Storage

Store indoors, protected from moisture, at temperatures between 45°F and 110°F (7°C and 43°C) and out of direct sunlight.

Limitations

- Protect from freezing.
- All surfaces must be sound, clean, dry and free from contamination. A thorough wire brushing, grinding, sandblasting or solvent cleaning may be required to expose clean, sound, virgin surfaces.
- Any questions regarding drying times, coverage rates and unique application techniques regarding the individual primers should be directed to Tremco Technical Services or your local Tremco Sales Representative.
- Do not apply over contaminated or damp surfaces.
- Do not thin.

Warranty

Tremco warrants its Products to be free of defects in materials, but makes no warranty as to appearance or color. Since methods of application and on-site conditions are beyond our control and can affect performance, Tremco makes no other warranty, expressed or implied, including warranties of MERCHANTABILITY and FITNESS FOR A PARTICULAR PURPOSE, with respect to Tremco Products. Tremco's sole obligation shall be, at its option, to replace or to refund the purchase price of the quantity of Tremco Product proven to be defective, and Tremco shall not be liable for any loss or damage.

Please refer to our website at www.tremcosealants.com for the most up-to-date Product Data Sheets.

NOTE: All Tremco Safety Data Sheets (SDS) are in alignment with the Globally Harmonized System of Classification and Labelling of Chemicals (GHS) requirements.

TYPICAL PHYSICAL PROPERTIES

PROPERTY @ 75°F, 50% RH

TYPICAL VALUE

Mix Ratio (A:B by Volume)

2:1

Total Solids

20%

VOC Content

68 g/L

Pot Life

4 hrs

Storage Temperature Range

45 °F (7 °C) minimum to 110 °F (43 °C) maximum

0117/MSUPDS-DC



Tremco Commercial Sealants & Waterproofing

3735 Green Rd
Beachwood OH 44122
216.292.5000 / 800.321.7906

1451 Jacobson Ave
Ashland OH 44805
419.289.2050 / 800.321.6357

220 Wicksteed Ave
Toronto ON M4H1G7
416.421.3300 / 800.363.3213

1445 Rue de Coulomb
Boucherville QC J4B 7L8
514.521.9555

www.tremcosealants.com