

Version: 1.2 Revision Date: 11/30/2018

# SAFETY DATA SHEET

#### 1. Identification

# Material name: TREMprime Silicone Metal Primer Material: 943202 011

#### Recommended use and restriction on use

**Recommended use:** Coatings **Restrictions on use:** Not known.

#### Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants 3735 Green Road Beachwood OH 44122 US

Contact person: Telephone: Emergency telephone number: EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

#### 2. Hazard(s) identification

#### **Hazard Classification**

Physical Hazards Flammable liquids

Category 3

#### **Health Hazards**

Acute toxicity (Inhalation - vapor)	Category 4
Germ Cell Mutagenicity	Category 1B
Carcinogenicity	Category 1A

#### **Unknown toxicity - Health**

Acute toxicity, oral	0.1 %
Acute toxicity, dermal	8.1 %
Acute toxicity, inhalation, vapor	13.2 %
Acute toxicity, inhalation, dust	100 %
or mist	

#### Label Elements

#### Hazard Symbol:





Version: 1.2 Revision Date: 11/30/2018

Signal Word:	Danger
Hazard Statement:	Flammable liquid and vapor. Harmful if inhaled. May cause genetic defects . May cause cancer.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. Call a POISON CENTER/doctor/ IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). In case of fire: Use to extinguish.
Storage:	Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
Hydrotreated heavy naphtha	64742-48-9	50 - <100%
Tetrabutyl titanate	5593-70-4	1 - <5%
Tetraethoxysilane	78-10-4	1 - <5%
Light Alkylate Naphtha	64741-66-8	1 - <5%
Ethyl alcohol	64-17-5	0.1 - <1%
n-Butanol	71-36-3	0.1 - <1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### 4. First-aid measures



Ingestion:	Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.
Inhalation:	Move to fresh air.
Skin Contact:	Wash skin thoroughly with soap and water. Take off immediately all contaminated clothing. If skin irritation occurs: Get medical advice/attention.
Eye contact:	Any material that contacts the eye should be washed out immediately with water. If easy to do, remove contact lenses. If eye irritation persists: Get medical advice/attention.
Most important symptoms/effect	ts, acute and delayed
Symptoms:	Respiratory tract irritation.
Indication of immediate medical a	attention and special treatment needed
Treatment:	Symptoms may be delayed.
5. Fire-fighting measures	
General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.
Suitable (and unsuitable) exting	uishing media
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.
Special protective equipment an	d precautions for firefighters
Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
6. Accidental release measure	s
Personal precautions, protective equipment and	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep

emergency procedures:

upwind.



Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.
7. Handling and storage	
Precautions for safe handling:	Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges.
Conditions for safe storage, including any incompatibilities:	Store locked up. Store in a well-ventilated place. Store in a cool place.

# 8. Exposure controls/personal protection

#### **Control Parameters**

#### **Occupational Exposure Limits**

Chemical Identity	Туре	Exposure Limit Values	Source
Tetraethoxysilane	TWA	10 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 850 mg	/m3 US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
Ethyl alcohol	STEL	1,000 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	1,000 ppm 1,900 mg	/m3 US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)
n-Butanol	TWA	20 ppm	US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm 300 mg	/m3 US. OSHA Table Z-1 Limits for Air
			Contaminants (29 CFR 1910.1000) (02 2006)



E.

-

Chemical name	Туре	Exposure Lin	nit Values	Source
Hydrotreated heavy naphtha	TWA		525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Tetraethoxysilane	TWA	10 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Tetraethoxysilane	TWA	10 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Tetraethoxysilane	TWA	10 ppm	85 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethyl alcohol	STEL	1,000 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Ethyl alcohol	STEL	1,000 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethyl alcohol	TWA	1,000 ppm	1,880 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
n-Butanol	CEILING	30 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	15 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
n-Butanol	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
n-Butanol	CEILING	50 ppm	152 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Chemical name	Туре	Exposure Lin	nit Values	Source
Hydrotreated heavy naphtha	TWA		525 mg/m3	Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Tetraethoxysilane	TWA	10 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Tetraethoxysilane	TWA	10 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Tetraethoxysilane	TWA	10 ppm	85 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Ethyl alcohol	STEL	1,000 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Ethyl alcohol	STEL	1,000 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
Ethyl alcohol	TWA	1,000 ppm	1,880 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
n-Butanol	CEILING	30 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	15 ppm		Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation



				296/97, as amended) (07 2007)
n-Butanol	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) (11 2010)
n-Butanol	CEILING	50 ppm - 7	152 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)

Appropriate Engineering<br/>ControlsObserve good industrial hygiene practices. Observe occupational exposure<br/>limits and minimize the risk of inhalation of vapors and mist. Mechanical<br/>ventilation or local exhaust ventilation may be required.

#### Individual protection measures, such as personal protective equipment

General information:	Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear suitable protective clothing.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke.

### 9. Physical and chemical properties

#### Appearance

Physical state:	liquid
Form:	liquid
Color:	Pale yellow
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	25 °C 77 °F
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explos	ive limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.



No data available.
No data available.
Vapors are heavier than air and may travel along the floor and in the bottom of containers.
0.79
Practically Insoluble
No data available.

# 10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Heat, sparks, flames.
Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.
•	

# 11. Toxicological information

Information on likely routes of exposure		
Inhalation:	In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.	
Skin Contact:	May be harmful in contact with skin. Causes mild skin irritation.	
Eye contact:	Eye contact is possible and should be avoided.	
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.	
Symptoms related to the physic	al, chemical and toxicological characteristics	
Inhalation:	No data available.	
Skin Contact:	No data available.	
Eye contact:	No data available.	
Ingestion:	No data available.	



#### Information on toxicological effects

#### Acute toxicity (list all possible routes of exposure)

Oral Product:	Not classified for acute toxicity based on available data.
<b>Specified substance(s):</b> Hydrotreated heavy naphtha	LD 50 (Rat): > 5,000 mg/kg
Tetrabutyl titanate	LD 50 (Rat): > 2,000 mg/kg
Tetraethoxysilane	LD 50 (Rat): > 2,500 mg/kg
Light Alkylate Naphtha	LD 50 (Rat): > 6,000 mg/kg
Ethyl alcohol	LD 50 (Rat): 10,470 mg/kg
n-Butanol	LD 50 (Rat): 2,292 mg/kg
Dermal Product:	Not classified for acute toxicity based on available data.
<b>Specified substance(s):</b> Hydrotreated heavy naphtha	LD 50 (Rabbit): > 2,000 mg/kg
Light Alkylate Naphtha	LD 50 (Rabbit): > 3,000 mg/kg
Ethyl alcohol	LD 50 (Rabbit): 17,100 mg/kg
n-Butanol	LD 50 (Rabbit): 3,430 mg/kg
Inhalation Product:	ATEmix: 8.52 mg/l
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.



#### Specified substance(s):

Hydrotreated heavy naphtha	in vivo (Rabbit): Study design not appropriate to classify skin irritation. Experimental result, Supporting study
Tetrabutyl titanate	in vivo (Rabbit): Highly irritating Experimental result, Weight of Evidence study
Light Alkylate Naphtha	in vivo (Rabbit): Irritating Experimental result, Key study
Ethyl alcohol	in vivo (Rabbit): Not irritant Experimental result, Key study
n-Butanol	Draize test (Rabbit): Category 2 Experimental result, Key study

#### Serious Eye Damage/Eye Irritation

Product: Specified substance(s):	No data available.
Hydrotreated heavy naphtha	Rabbit, 24 - 72 hrs: Not irritating
Tetraethoxysilane	Rabbit, 24 - 72 hrs: Not irritating
Light Alkylate Naphtha	Rabbit: Not irritating
n-Butanol	Rabbit, 24 - 72 hrs: Category 1
Respiratory or Skin Sensitizatior Product:	n No data available.

Carcinogenicity Product:

No data available.

#### IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

Ethyl alcohol

Overall evaluation: Carcinogenic to humans. Overall evaluation: Carcinogenic to humans.

#### US. National Toxicology Program (NTP) Report on Carcinogens: Ethyl alcohol Known To Be Human Carcinogen.

# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified



#### Germ Cell Mutagenicity

In vitro Product:	No data available.	
In vivo Product:	No data available.	
Reproductive toxicity Product:	No data available.	
Specific Target Organ Toxicity - Single Exposure Product: No data available.		
Specific Target Organ Toxicity - Repeated Exposure Product: No data available.		
Aspiration Hazard Product:	No data available.	
Other effects:	No data available.	

## 12. Ecological information

#### **Ecotoxicity:**

#### Acute hazards to the aquatic environment:

Fish Product:	No data available.
Specified substance(s): Ethyl alcohol	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13,480 mg/l Mortality
n-Butanol	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 1,630 - 1,840 mg/l Mortality
Aquatic Invertebrates Product:	No data available.
Specified substance(s): n-Butanol	EC 50 (Water flea (Daphnia magna), 48 h): 1,897 - 2,072 mg/l Intoxication

Chronic hazards to the aquatic environment:



Fish Product:	No data available.
<b>Specified substance(s):</b> Hydrotreated heavy naphtha	LL 50 (Pimephales promelas, 14 d): 5.2 mg/l Experimental result, Supporting study NOAEL (Pimephales promelas, 14 d): 2.6 mg/l Experimental result, Supporting study NOAEL (Daphnia magna, 21 d): 2.6 mg/l Other, Key study EC 50 (Daphnia magna, 21 d): 10 mg/l Other, Key study
Light Alkylate Naphtha	LL 50 (Pimephales promelas, 14 d): 5.2 mg/l Experimental result, Supporting study
Aquatic Invertebrates Product:	No data available.
Toxicity to Aquatic Plants Product:	No data available.
Persistence and Degradability	
Biodegradation Product:	No data available.
BOD/COD Ratio Product:	No data available.
Bioaccumulative potential Bioconcentration Factor (BC Product:	F) No data available.
Partition Coefficient n-octanol / w Product:	v <b>ater (log Kow)</b> No data available.
Specified substance(s): Ethyl alcohol	Log Kow: -0.31
n-Butanol	Log Kow: 0.88
Mobility in soil:	No data available.
Other adverse effects:	No data available.
13. Disposal considerations	
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.



Contaminated Packaging: No data available.

## 14. Transport information

#### TDG:

UN1139, COATING SOLUTION, 3, PG III

#### CFR / DOT:

UN1139, Coating solution, 3, PG III

#### IMDG:

UN1139, COATING SOLUTION, 3, PG III

#### Further Information:

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

#### 15. Regulatory information

#### **US Federal Regulations**

### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.

# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

None present or none present in regulated quantities.

#### CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	<b>Reportable quantity</b>
Ethyl alcohol	100 lbs.
n-Butanol	5000 lbs.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Hazard categories

Fire Hazard Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard Flammable (gases, aerosols, liquids, or solids) Acute toxicity (any route or exposure) Germ Cell Mutagenicity Carcinogenicity Hazards Not Otherwise Classified (HNOC)

#### SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.



# SARA 304 Emergency Release Notification

Chemical IdentityReportable quantityEthyl alcohol100 lbs.n-Butanol5000 lbs.

#### SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Hydrotreated heavy	10000 lbs
naphtha	
Tetrabutyl titanate	10000 lbs
Tetraethoxysilane	10000 lbs
Light Alkylate Naphtha	10000 lbs
Ethyl alcohol	10000 lbs
n-Butanol	10000 lbs

#### SARA 313 (TRI Reporting)

None present or none present in regulated quantities.

#### Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) None present or none present in regulated quantities.

#### Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)

None present or none present in regulated quantities.

#### **US State Regulations**

#### **US. California Proposition 65**

#### WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

#### US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity Tetraethoxysilane Ethyl alcohol

#### **US. Massachusetts RTK - Substance List**

Chemical Identity Tetraethoxysilane

#### US. Pennsylvania RTK - Hazardous Substances

# Chemical Identity

Hydrotreated heavy naphtha Tetraethoxysilane

US. Rhode Island RTK

#### Chemical Identity Tetraethoxysilane

#### International regulations



#### Montreal protocol

Not applicable

## Stockholm convention

Not applicable

# Rotterdam convention

Not applicable

# Kyoto protocol

Not applicable

## VOC:

Regulatory VOC (less water and exempt solvent)	:	671 g/l
VOC Method 310	:	84.90 %



Version: 1.2 Revision Date: 11/30/2018

**Inventory Status:** Australia AICS: One or more components in this product are not listed on or exempt from the Inventory. EINECS, ELINCS or NLP: One or more components in this product are not listed on or exempt from the Inventory. Japan (ENCS) List: One or more components in this product are not listed on or exempt from the Inventory. China Inv. Existing Chemical Substances: One or more components in this product are not listed on or exempt from the Inventory. Korea Existing Chemicals Inv. (KECI): One or more components in this product are not listed on or exempt from the Inventory. Canada NDSL Inventory: One or more components in this product are not listed on or exempt from the Inventory. Philippines PICCS: One or more components in this product are not listed on or exempt from the Inventory. New Zealand Inventory of Chemicals: One or more components in this product are not listed on or exempt from the Inventory. Japan ISHL Listing: One or more components in this product are not listed on or exempt from the Inventory. Japan Pharmacopoeia Listing: One or more components in this product are not listed on or exempt from the Inventory. Mexico INSQ: One or more components in this product are not listed on or exempt from the Inventory. One or more components in this product are Ontario Inventory: not listed on or exempt from the Inventory. Taiwan Chemical Substance Inventory: One or more components in this product are not listed on or exempt from the Inventory. Canada DSL Inventory List: All components in this product are listed on or exempt from the Inventory. US TSCA Inventory: All components in this product are listed on or exempt from the Inventory.



# 16.Other information, including date of preparation or last revision

Revision Date:	11/30/2018
Version #:	1.2
Further Information:	No data available.
Disclaimer:	For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.