

# SAFETY DATA SHEET

# 1. Identification

# Material name: TREMprime Silicone Porous Primer Material: 943303 506

# Recommended use and restriction on use

**Recommended use:** Coatings **Restrictions on use:** Not known.

# Manufacturer/Importer/Supplier/Distributor Information

Tremco U.S Sealants 3735 Green Road Beachwood OH 44122 US

Contact person: Telephone: Emergency telephone number: EH&S Department 216-292-5000 1-800-424-9300 (US); 1-613-996-6666 (Canada)

# 2. Hazard(s) identification

# **Hazard Classification**

Physical Hazards Flammable liquids

Category 2

# **Health Hazards**

Skin Corrosion/Irritation	Category 2
Carcinogenicity	Category 1A
Toxic to reproduction	Category 2

# **Unknown toxicity - Health**

Acute toxicity, oral	26.3 %
Acute toxicity, dermal	27.8 %
Acute toxicity, inhalation, vapor	88.7 %
Acute toxicity, inhalation, dust or mist	98.5 %

# Label Elements

# Hazard Symbol:





Signal Word:	Danger
Hazard Statement	Highly flammable liquid and vapor. Causes skin irritation. May cause cancer. Suspected of damaging fertility or the unborn child.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Use explosion-proof [electrical/ventilating/lighting/] equipment. Use non-sparking tools. Take action to prevent static discharges. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required.
Response:	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower]. If skin irritation occurs: Get medical advice/attention. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing. In case of fire: Use to extinguish.
Storage:	Store in a well-ventilated place. Keep cool. Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	Static accumulating flammable liquid can become electrostatically charged even in bonded and grounded equipment. Sparks may ignite liquid and vapor. May cause flash fire or explosion.

# 3. Composition/information on ingredients

# **Mixtures**

Chemical Identity	CAS number	Content in percent (%)*
Acetone	67-64-1	40 - 70%
Toluene	108-88-3	10 - 30%
Tetraethoxysilane	78-10-4	1 - 5%
Ethyl alcohol	64-17-5	0.1 - 1%

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

# 4. First-aid measures

# Ingestion:

Call a POISON CENTER/doctor if you feel unwell. Rinse mouth.

Inhalation:

Move to fresh air.



Skin Contact:	Take off immediately all contaminated clothing. Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.	
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.	
Most important symptoms/effect	s, acute and delayed	
Symptoms:	Respiratory tract irritation. Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.	
Indication of immediate medical a	ttention and special treatment needed	
Treatment:	Symptoms may be delayed.	
5. Fire-fighting measures		
General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Water may be ineffective in fighting the fire. Fight fire from a protected location. Move containers from fire area if you can do so without risk.	
Suitable (and unsuitable) exting	uishing media	
Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.	
Unsuitable extinguishing media:	Avoid water in straight hose stream; will scatter and spread fire.	
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back. Vapors may cause a flash fire or ignite explosively. Prevent buildup of vapors or gases to explosive concentrations.	
Special protective equipment an	d precautions for firefighters	
Special fire fighting procedures:	No data available.	
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.	
6. Accidental release measure	S	
Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep upauthorized personnel away	

appropriate protective clothing. Keep unauthorized personnel away.



Methods and material for containment and cleaning up:	Dam and absorb spillages with sand, earth or other non-combustible material. Collect spillage in containers, seal securely and deliver for disposal according to local regulations.
Notification Procedures:	In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.
Environmental Precautions:	Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so.
7. Handling and storage	
Precautions for safe handling:	Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground and bond container and receiving equipment. Take precautionary measures against static discharges. Avoid contact with skin. Wash hands thoroughly after handling.
Conditions for safe storage, including any incompatibilities:	Store locked up. Store in a well-ventilated place. Store in a cool place.

# 8. Exposure controls/personal protection

# **Control Parameters**

# Occupational Exposure Limits

Chemical Identity	Туре	Exposure Lir	nit Values	Source
Acetone	TWA	250 ppm		US. ACGIH Threshold Limit Values (03 2015)
	STEL	500 ppm		US. ACGIH Threshold Limit Values (03 2015)
	PEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1 Limits for Air
				Contaminants (29 CFR 1910.1000) (02 2006)
Toluene	TWA	20 ppm		US. ACGIH Threshold Limit Values (2011)
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02
				2006)
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02
	-			2006)
	MAX.	500 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02
	CONC			2006)
Tetraethoxysilane	TWA	10 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	100 ppm	850 mg/m3	US. OSHA Table Z-1 Limits for Air
			-	Contaminants (29 CFR 1910.1000) (02 2006)
Ethyl alcohol	STEL	1,000 ppm		US. ACGIH Threshold Limit Values (2011)
	PEL	1,000 ppm	1,900 mg/m3	US. OSHA Table Z-1 Limits for Air
			Ū	Contaminants (29 CFR 1910.1000) (02 2006)

Chemical name	Туре	Exposure Limit Values	Source
Acetone	STEL	500 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
	TWA	250 ppm	Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation



				296/97, as amended) (07 2007)
Acetone	TWA	500 ppm 1	,190 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
	STEL	1,000 ppm 2	2,380 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Acetone	TWA	250 ppm		Canada. Ontario OELs. (Control of Exposure Biological or Chemical Agents) (08 2017)
	STEL	500 ppm		Canada. Ontario OELs. (Control of Exposure Biological or Chemical Agents) (08 2017)
Toluene	TWA	20 ppm		Canada. British Columbia OELs. (Occupationa Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Toluene	TWA	20 ppm		Canada. Ontario OELs. (Control of Exposure Biological or Chemical Agents) (11 2010)
Toluene	TWA	50 ppm	188 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) (09 2017)
Tetraethoxysilane	TWA	10 ppm		Canada. British Columbia OELs. (Occupation Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Tetraethoxysilane	TWA	10 ppm		Canada. Ontario OELs. (Control of Exposure Biological or Chemical Agents) (11 2010)
Tetraethoxysilane	TWA	10 ppm	85 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Wor Environment) (09 2017)
Ethyl alcohol	STEL	1,000 ppm		Canada. British Columbia OELs. (Occupation. Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) (07 2007)
Ethyl alcohol	STEL	1,000 ppm		Canada. Ontario OELs. (Control of Exposure Biological or Chemical Agents) (11 2010)
Ethyl alcohol	TWA	1,000 ppm 1	,880 mg/m3	Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Wor Environment) (09 2017)

# **Biological Limit Values**

Chemical Identity	Exposure Limit Values	Source
Acetone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BEI (03 2015)
Toluene (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEI (03 2013)
Toluene (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEI (03 2013)
Toluene (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEI (03 2013)

# Appropriate Engineering Controls

Observe good industrial hygiene practices. Observe occupational exposure limits and minimize the risk of inhalation of vapors and mist. Mechanical ventilation or local exhaust ventilation may be required.



# Individual protection measures, such as personal protective equipment

General information:	Use explosion-proof ventilation equipment. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide easy access to water supply and eye wash facilities.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection Hand Protection:	Use suitable protective gloves if risk of skin contact.
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Observe good industrial hygiene practices. Wash hands before breaks and immediately after handling the product. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin.

# 9. Physical and chemical properties

Appearance	
Physical state:	liquid
Form:	liquid
Color:	Colorless
Odor:	Mild petroleum/solvent
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	56 °C 133 °F
Flash Point:	-18 °C 0 °F(Pensky-Martens Closed Cup)
Evaporation rate:	Slower than Ether
Flammability (solid, gas):	No
Upper/lower limit on flammability or explose	sive limits
Flammability limit - upper (%):	13 %(V)
Flammability limit - lower (%):	2.3 %(V)
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	No data available.
Vapor density:	Vapors are heavier than air and may travel along the floor and in the bottom of containers.



Relative density: Solubility(ies)	0.9	
Solubility in water:	Practically Insoluble	
Solubility (other):	No data available.	
Partition coefficient (n-octanol/v		
Auto-ignition temperature:	No data available.	
Decomposition temperature:	No data available.	
Viscosity:	No data available.	
10. Stability and reactivity		
Reactivity:	No data available.	
Chemical Stability:	Material is stable under normal conditions.	
Possibility of hazardous reactions:	No data available.	
Conditions to avoid:	Heat, sparks, flames.	
Incompatible Materials:	Strong acids. Avoid contact with oxidizing agents (e.g. nitric acid, peroxides and chromates). Strong bases.	
Hazardous Decomposition Products:	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.	
11. Toxicological information		
Information on likely routes of e Inhalation:	exposure In high concentrations, vapors, fumes or mists may irritate nose, throat and mucus membranes.	
Skin Contact:	Causes skin irritation.	
Eye contact:	Eye contact is possible and should be avoided.	
Ingestion:	May be ingested by accident. Ingestion may cause irritation and malaise.	
Symptoms related to the physic	al, chemical and toxicological characteristics	
Inhalation:	No data available.	
Skin Contact:	No data available.	
Eye contact:	No data available.	

Ingestion: No data available.



# Information on toxicological effects

# Acute toxicity (list all possible routes of exposure)

Oral Product:	ATEmix: 122,833.5 mg/kg
Dermal Product:	ATEmix: 144,400 mg/kg
Inhalation Product:	Not classified for acute toxicity based on available data.
Specified substance(s): Acetone	LC 50 (Rat): 50.1 mg/l
Toluene	LC 50 (Rat): 25.7 mg/l
Ethyl alcohol	LC 50 (Rat): 116.9 mg/l
Repeated dose toxicity Product:	No data available.
Skin Corrosion/Irritation Product:	No data available.
Specified substance(s): Acetone	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Toluene	in vivo (Rabbit): Irritating Experimental result, Key study
Ethyl alcohol	in vivo (Rabbit): Not irritant Experimental result, Key study
Serious Eye Damage/Eye Irritati	on

# Product: No data available. Specified substance(s): Acetone Irritating Toluene Rabbit, 24 - 72 hrs: Not irritating

# Respiratory or Skin Sensitization Product: No data available.



Carcinogenicity Product:	No data available.
IARC Monographs on the Evaluation	ation of Carcinogenic Risks to Humans:
Ethyl alcohol	Overall evaluation: Carcinogenic to humans. Overall evaluation: Carcinogenic to humans.
US. National Toxicology Program Ethyl alcohol	<b>n (NTP) Report on Carcinogens:</b> Known To Be Human Carcinogen.
US. OSHA Specifically Regulate No carcinogenic component	d Substances (29 CFR 1910.1001-1050): s identified
Germ Cell Mutagenicity	
In vitro Product:	No data available.
In vivo Product:	No data available.
Reproductive toxicity Product:	Suspected of damaging fertility or the unborn child.
Specific Target Organ Toxicity - Product:	Single Exposure No data available.
Specific Target Organ Toxicity - Product:	Repeated Exposure No data available.
Aspiration Hazard Product:	No data available.
Other effects:	No data available.

# 12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:



Fish Product:	No data available.
Specified substance(s): Acetone	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 5,490 - 7,030 mg/l Mortality
Toluene	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 20.5 - 23.8 mg/l Mortality
Ethyl alcohol	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 13,480 mg/l Mortality
Aquatic Invertebrates Product:	No data available.
Specified substance(s): Acetone	EC 50 (Water flea (Daphnia magna), 48 h): 10,294 - 17,704 mg/l Intoxication
Toluene	LC 50 (Water flea (Daphnia magna), 24 h): 240 - 420 mg/l Mortality
Chronic hazards to the aquati	c environment:
Fish Product:	No data available.
Specified substance(s): Toluene	LOAEL (Oncorhynchus kisutch, 40 d): 2.77 mg/l Experimental result, Key study NOAEL (Pimephales promelas, 32 d): 4 mg/l Experimental result, Supporting study

LOAEL (Pimephales promelas, 32 d): 6 mg/l Experimental result, Supporting study NOAEL (Oncorhynchus kisutch, 40 d): 1.39 mg/l Experimental result, Key

# Aquatic Invertebrates Product: No data available.

study

Toxicity to Aquatic PlantsProduct:No data available.

# Persistence and Degradability

Biodegradation	
Product:	No data available.

BOD/COD Ratio Product: No data available.

# Bioaccumulative potential Bioconcentration Factor (BCF) Product: No data available.



Specified substance(s): Toluene	Green algae (Selenastrum capricornutum), Bioconcentration Factor (BCF): 3,016 (Static)
Partition Coefficient n-octanol / v Product:	vater (log Kow) No data available.
Specified substance(s): Acetone	Log Kow: -0.24
Toluene	Log Kow: 2.73
Ethyl alcohol	Log Kow: -0.31
Mobility in soil:	No data available.
Other adverse effects:	No data available.
13. Disposal considerations	
Disposal instructions:	Dispose of waste at an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Contaminated Packaging:	No data available.
14. Transport information	

# TDG:

UN1139, COATING SOLUTION, 3, PG II

# CFR / DOT:

UN1139, Coating solution, 3, PG II

# IMDG:

UN1139, COATING SOLUTION, 3, PG II

# **Further Information:**

The above shipping description may not be accurate for all container sizes and all modes of transportation. Please refer to Bill of Lading.

# 15. Regulatory information

# **US Federal Regulations**

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

None present or none present in regulated quantities.



### US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

# Chemical Identity

Benzene

OSHA hazard(s) Blood respiratory tract irritation Central nervous system Flammability Cancer Skin Aspiration Eye

# CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	<b>Reportable quantity</b>
Acetone	5000 lbs.
Toluene	1000 lbs.
Ethyl alcohol	100 lbs.
Benzene	10 lbs.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

### **Hazard categories**

Fire Hazard Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard

# SARA 302 Extremely Hazardous Substance

None present or none present in regulated quantities.

### SARA 304 Emergency Release Notification

Chemical Identity	<b>Reportable quantity</b>
Acetone	5000 lbs.
Toluene	1000 lbs.
Ethyl alcohol	100 lbs.
Benzene	10 lbs.

### SARA 311/312 Hazardous Chemical

Chemical Identity	Threshold Planning Quantity
Acetone	10000 lbs
Toluene	10000 lbs
Tetraethoxysilane	10000 lbs
Ethyl alcohol	10000 lbs

# SARA 313 (TRI Reporting)

# **Chemical Identity**

Toluene

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130) None present or none present in regulated quantities.

#### Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) None present or none present in regulated quantities.



# **US State Regulations**

**US. California Proposition 65** 



#### WARNING

Cancer and Reproductive Harm - www.P65Warnings.ca.gov

# US. New Jersey Worker and Community Right-to-Know Act

<u>Chemical Identity</u> Acetone Toluene Tetraethoxysilane Ethyl alcohol

# **US. Massachusetts RTK - Substance List**

Chemical Identity Acetone Toluene Tetraethoxysilane Benzene

#### US. Pennsylvania RTK - Hazardous Substances

<u>Chemical Identity</u> Acetone Toluene Tetraethoxysilane

# US. Rhode Island RTK

<u>Chemical Identity</u> Acetone Toluene Tetraethoxysilane

# International regulations

# **Montreal protocol**

Not applicable

# Stockholm convention

Not applicable

# Rotterdam convention

Not applicable

# Kyoto protocol

Not applicable

# VOC:

Regulatory VOC (less water and exempt solvent)	:	252 g/l
VOC Method 310	:	11.30 %



Inventory Status: Australia AICS:	All components in this product are listed on or exempt from the Inventory.
Canada DSL Inventory List:	All components in this product are listed on or exempt from the Inventory.
EINECS, ELINCS or NLP:	One or more components in this product are not listed on or exempt from the Inventory.
Japan (ENCS) List:	One or more components in this product are not listed on or exempt from the Inventory.
China Inv. Existing Chemical Substances:	All components in this product are listed on or exempt from the Inventory.
Korea Existing Chemicals Inv. (KECI):	All components in this product are listed on or exempt from the Inventory.
Canada NDSL Inventory:	One or more components in this product are not listed on or exempt from the Inventory.
Philippines PICCS:	All components in this product are listed on or exempt from the Inventory.
US TSCA Inventory:	All components in this product are listed on or exempt from the Inventory.
New Zealand Inventory of Chemicals:	All components in this product are listed on or exempt from the Inventory.
Japan ISHL Listing:	One or more components in this product are not listed on or exempt from the Inventory.
Japan Pharmacopoeia Listing:	One or more components in this product are not listed on or exempt from the Inventory.

# 16.Other information, including date of preparation or last revision

Revision Date:	11/30/2018
Version #:	1.2
Further Information:	No data available.



**Disclaimer:** 

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.