

SAFETY DATA SHEET

BIO-CIRCLE® A division of Walter Surface Technologies

OPEN GEAR

Section 1. Identification

GHS product identifier : OPEN GEAR
Product code : 53-E 102 (400 mL)

SDS no. : L-16E
Product type : Aerosol

Identified uses

High load drive lubricant.

Manufacturer : Walter Surface Technologies Inc.

Bio-Circle - A Division of Walter Surface Technologies Inc.

810 Day Hill Road Windsor, CT 06095 United States

General Information: 18665925837

www.walter.com

Emergency telephone number (with hours of operation) : INFOTRAC® 1-800-535-5053, Outside U.S.A. call collect: 1-352-323-3500

24 hours/day, 7 days/week.

Section 2. Hazards identification

OSHA/HCS status

: This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture

: FLAMMABLE AEROSOLS - Category 1
GASES UNDER PRESSURE - Compressed gas
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A

GHS label elements

Hazard pictograms



Signal word

: Danger

Hazard statements

H222 - Extremely flammable aerosol.

H280 - Contains gas under pressure; may explode if heated.

H319 - Causes serious eve irritation.

Precautionary statements

General

: Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

Prevention

: P280 - Wear eye or face protection.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P251 - Pressurized container: Do not pierce or burn, even after use. P211 - Do not spray on an open flame or other ignition source.

P264 - Wash hands thoroughly after handling.







Section 2. Hazards identification

: P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Response

Remove contact lenses, if present and easy to do. Continue rinsing.

P337 + P313 - If eye irritation persists: Get medical attention.

: P410 - Protect from sunlight. Storage

P412 - Do not expose to temperatures exceeding 50°C/122°F.

P403 - Store in a well-ventilated place.

Disposal : Not applicable. **Hazards not otherwise** : None known.

classified

Section 3. Composition/information on ingredients

Substance/mixture : Mixture

Product code : 53-E 102 (400 mL)

CAS number/other identifiers

CAS number : Not applicable.

Ingredient name	%	CAS number
Naphtha (petroleum), hydrotreated light Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts		64742-49-0 68457-79-4

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Continue to rinse for at least 20 minutes. Get medical attention.

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial

respiration or oxygen by trained personnel. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical

attention immediately.

Skin contact : Flush contaminated skin with plenty of water. Wash contaminated clothing thoroughly

with water before removing it, or wear gloves. Continue to rinse for at least 20 minutes.

Get medical attention. Wash clothing before reuse.

Wash out mouth with water. Remove victim to fresh air and keep at rest in a position Ingestion comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if adverse health effects persist or are severe.

Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately.

Most important symptoms/effects, acute and delayed

Potential acute health effects

Eye contact : Causes serious eye irritation.







Section 4. First aid measures

Inhalation : No known significant effects or critical hazards. Skin contact : No known significant effects or critical hazards.

Ingestion : Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

Eve contact : Adverse symptoms may include the following:

> pain or irritation watering redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contact : No known significant effects or critical hazards. Ingestion : No known significant effects or critical hazards.

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments : No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training. It may

: In case of fire, use foam, dry chemical or carbon dioxide.

be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

See toxicological information (Section 11)

Section 5. Fire-fighting measures

Extinguishing media

Suitable extinguishing

media

Unsuitable extinguishing

media

: Do not use water jet.

Specific hazards arising from the chemical

: Extremely flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products Decomposition products may include the following materials:

carbon dioxide carbon monoxide Sulfur oxides phosphorus oxides metal oxide/oxides

Special protective actions for fire-fighters

Special protective equipment for fire-fighters Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.





Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. In the case of aerosols being ruptured, care should be taken due to the rapid escape of the pressurized contents and propellant. If a large number of containers are ruptured, treat as a bulk material spillage according to the instructions in the clean-up section. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

For emergency responders:

If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

Environmental precautions

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

Section 7. Handling and storage

Precautions for safe handling

Protective measures

Put on appropriate personal protective equipment (see Section 8). Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing gas. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures. Remove contaminated clothing and protective equipment before entering eating areas.





Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities

: Store in accordance with local regulations. Store away from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Protect from sunlight. Eliminate all ignition sources. Use appropriate containment to avoid environmental contamination.

Section 8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

None.

Appropriate engineering controls

: Use only with adequate ventilation (typically 10 air changes per hour). If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. In case of insufficient ventilation, wear suitable respiratory equipment.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

Skin protection **Hand protection**

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. Recommended: Nitrile gloves. (Permeation time > 8 hours)

Body protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear antistatic protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves.

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Use a NIOSH/MSHA approved respirator if there is a risk of exposure at levels exceeding the exposure limits. Advice should be sought from respiratory protection specialists.







Section 9. Physical and chemical properties

Appearance

Physical state : Liquid. [Aerosol.]

Color Gray.

Odor : Characteristic. : Not available. **Odor threshold** pН : Not applicable. **Melting point** : Not available. : Not applicable. **Boiling point**

: Closed cup: -60°C (-76°F) Flash point

: Not applicable. **Evaporation rate**

Flammability (solid, gas) : Extremely flammable aerosol.

: Lower: 1.4% Lower and upper explosive (flammable) limits Upper: 32%

: 250 kPa (1875.2 mm Hg) [@ 20°C (68°F)] Vapor pressure

Vapor density : Not available.

Density : 0.72 g/ml @ 20°C (68°F)

: Insoluble in the following materials: cold water and hot water. Solubility

Partition coefficient: n-

Decomposition temperature

octanol/water

Auto-ignition temperature : 510°C (950°F) : Not available.

: Not available.

: Dynamic (room temperature): 255 cP (Aerosol), 116000 cP (Liquid) **Viscosity**

VOC content (g/L)

Aerosol product

Type of aerosol : Spray **Heat of combustion** : 15.92 kJ/g

Section 10. Stability and reactivity

Reactivity : No specific test data related to reactivity available for this product or its ingredients.

Chemical stability : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid : Avoid all possible sources of ignition (spark or flame).

Incompatible materials : Reactive or incompatible with the following materials: oxidizing materials and acids.

Hazardous decomposition

: Under normal conditions of storage and use, hazardous decomposition products should

products not be produced.







Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Phosphorodithioic acid, mixed O,O- bis(iso-Bu and pentyl) esters, zinc salts	LD50 Oral	Rat	3.6 g/kg	-

Irritation/Corrosion

There is no data available.

Sensitization

There is no data available.

Carcinogenicity

Classification

Product/ingredient name	OSHA	IARC	NTP	ACGIH	EPA	NIOSH
Isobutane	-	-	-	-	-	None.
Silicon dioxide	-	3	-	-	-	-

Specific target organ toxicity (single exposure)

There is no data available.

Specific target organ toxicity (repeated exposure)

There is no data available.

Aspiration hazard

Name	Result
Naphtha (petroleum), hydrotreated light	ASPIRATION HAZARD - Category 1

Information on the likely routes of exposure

: Dermal contact. Eye contact. Inhalation. Ingestion.

Potential acute health effects

Eye contact : Causes serious eye irritation.

Inhalation : No known significant effects or critical hazards.Skin contact : No known significant effects or critical hazards.

Ingestion: Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : Adverse symptoms may include the following:

pain or irritation watering

redness

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Skin contactIngestionNo known significant effects or critical hazards.No known significant effects or critical hazards.

<u>Delayed and immediate effects and also chronic effects from short and long term exposure</u> <u>Short term exposure</u>







Section 11. Toxicological information

Potential immediate

effects

: No known significant effects or critical hazards.

Potential delayed effects

: No known significant effects or critical hazards.

Long term exposure

Potential immediate

effects

: No known significant effects or critical hazards.

Potential delayed effects : No known significant effects or critical hazards.

Potential chronic health effects

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Teratogenicity : No known significant effects or critical hazards.
 Developmental effects : No known significant effects or critical hazards.
 Fertility effects : No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Route	ATE value
Oral	276923.1 mg/kg

Section 12. Ecological information

Toxicity

There is no data available.

Persistence and degradability

There is no data available.

Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Naphtha (petroleum), hydrotreated light	2.2 to 5.2	10 to 2500	high
Phosphorodithioic acid, mixed O,O-bis (iso-Bu and pentyl) esters, zinc salts	0.69	-	low

Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No known significant effects or critical hazards.





Section 13. Disposal considerations

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Do not puncture or incinerate container.

Section 14. Transport information

	DOT Classification	IMDG	IATA
UN number	UN1950	UN1950	UN1950
UN proper shipping name	Aerosols, flammable (each not exceeding 1 L capacity)	Aerosols, flammable (each not exceeding 1 L capacity)	Aerosols, flammable (each not exceeding 1 L capacity)
Transport hazard class(es)	2.1	2.1	2.1
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Additional information	-	-	-

AERG: 126

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage. Protect from freezing. Freezing will damage product and render it unusable.

Transport in bulk according: Not available. to Annex II of MARPOL 73/78 and the IBC Code

Section 15. Regulatory information

U.S. Federal regulations

: TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 307: Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts

Clean Air Act (CAA) 112 regulated flammable substances: Butane; Propane; Isobutane







Section 15. Regulatory information

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs)

: Not listed

Clean Air Act Section 602

Class I Substances

: Not listed

Clean Air Act Section 602

Class II Substances

: Not listed

Class II Substances

DEA List I Chemicals (Precursor Chemicals)

: Not listed

(Precursor Chemicals)

DEA List II Chemicals (Essential Chemicals)

: Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Fire hazard

Sudden release of pressure Immediate (acute) health hazard

Composition/information on ingredients

Name	%	Fire hazard	Sudden release of pressure		Immediate (acute) health hazard	Delayed (chronic) health hazard
Naphtha (petroleum), hydrotreated light Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	10 - 30 1 - 5	Yes. No.		No. No.	No. Yes.	No. No.

SARA 313

	Product name	CAS number	%
Form R - Reporting requirements	Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4	1 - 5
Supplier notification	Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts	68457-79-4	1 - 5

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

Massachusetts : The following components are listed: Natural graphite; Silicon dioxide; Butane; Propane; Isobutane

New York : None of the components are listed.

New Jersey : The following components are listed: Natural graphite; Phosphorodithioic acid, mixed O,

O-bis(iso-Bu and pentyl) esters, zinc salts; Butane; Propane; Isobutane

Pennsylvania: The following components are listed: Natural graphite; Silicon dioxide; Phosphorodithioic acid, mixed O,O-bis(iso-Bu and pentyl) esters, zinc salts; Butane; Propane; Isobutane

California Prop. 65

No products were found.

International lists







Section 15. Regulatory information

National inventory

Australia : All components are listed or exempted.

Canada : All components are listed or exempted.

China : All components are listed or exempted.

Europe : All components are listed or exempted.

New Zealand : All components are listed or exempted.

Philippines : All components are listed or exempted.

Republic of Korea : All components are listed or exempted.

Section 16. Other information

History

Date of issue mm/dd/yyyy : 12/15/2014

Version : 1

Prepared by : KMK Regulatory Services Inc.

Key to abbreviations : ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

UN = United Nations

Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

