

SAFETY DATA SHEET

Page 1 of 3

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product:SEALMASTIC™ SEMI-MASTIC™Part Number: 6320055Manufacturer:W. R. MEADOWS, INC.Address: 300 Industrial Drive

Hampshire, Illinois 60140

Telephone: (847) 214-2100 In case of emergency, dial (800) 424-9300 (CHEMTREC)

Revision Date: 10/26/2021

HMIS

Product Use: Dampproofing for Concrete

SECTION 2: HAZARDS IDENTIFICATION/EXPOSURE LIMITS

Health	1	DANGER!				
Flammability	2	Causes skin irritation. (Category 2)				
Reactivity	[0]	Flammable liquid and vapor. (Category 3)				
Personal Protection	1 1	Harmful if inhaled. (Category 4)				
		May be fatal if swallowed and enters airway (Category 1				

HAZARD STATEMENTS

May be fatal if swallowed and enters airway. (Category 1)

PRECAUTIONARY STATEMENTS:
Use only in well-ventilated areas.

Avoid breathing vapors and direct contact.

Store in well-ventilated location.

Wear appropriate personal protective equipment.

Control vapors in confined spaces utilizing mechanical ventilation.

	SECTION 3: HAZARDS COMPONENTS					
		% by	SARA	Vapor Pressure	LEL	
Chemical Name:	CAS Number	<u>Weight</u>	<u>313</u>	(mm Hg@20°C)	(@25°C)	
 Mineral Spirits 	64742-47-8	30-60	No	2.6	0.75	
2. Petroleum Asphalt	8052-42-4	40-70	No	N/A	N/A	

N/A = Not Applicable

Under the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1966 (SARA) and 40 CFR Part 372, chemicals listed on the 313 List (40 CFR Part 373.65) are identified under the heading "SARA 313."

SECTION 4: EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT: Flush eyes with water for fifteen (15) minutes. If symptoms persist, seek medical attention.

SKIN CONTACT: Wash affected areas with mild soap and water. Remove contaminated shoes/clothing. If symptoms persist, seek medical attention.

INHALATION: If respiratory symptoms develop, move affected individual from exposure source and into fresh air. If symptoms persist, seek medical attention.

INGESTION: Dilute with liquid unless the victim is unconscious or very drowsy. Do not induce vomiting. If vomiting spontaneously occurs, prevent lung aspiration. Seek immediate medical attention.

MOST IMPORTANT SYMPTOMS/EFFECTS. ACUTE AND CHRONIC: See Section Eleven for Symptoms/Effects.

SECTION 5: FIRE AND EXPLOSIVES HAZARDS

FLASHPOINT: 100 °F

EXTINGUISHING MEDIA: Water fog, foam, dry chemical.

CHEMICAL/COMBUSTION HAZARDS: Carbon monoxide, carbon dioxide, oxides/compounds of nitrogen/sulfur, and

incomplete combustion products.

PRECAUTIONS/PERSONAL PROTECTIVE EQUIPMENT: Avoid smoke inhalation. Use appropriate personal protective equipment.

SECTION 6: ACCIDENTAL RELEASE MEASURES

SPILL OR LEAK PROCEDURES: Avoid direct contact. Remove ignition sources. Dike and contain spilled material. Remove source of pill if safe to do so. Apply absorbent and place clean-up material in sealed/marked containers for proper disposal.

SECTION 7: HANDLING AND STORAGE

SAFE HANDLING PROCEDURES: Avoid direct contact.

SAFE STORAGE: Keep containers closed when not in use. Keep away from ignition sources.



SAFETY DATA SHEET								
Date of Preparation:			Page 2 c					6320055
	SECTI	ON 8: EXPOSU	RE CONTRO	LS/PERS	ONAL PROT	ECTION		
		OSHA				ACGI		
<u>Chemical Name</u> :	<u>PEL</u>	PEL/CEILING	PEL/STEL	<u>SKIN</u>	<u>TWA</u>	TLV/CEILING	TLV/STEL	<u>SKIN</u>
1. Mineral Spirits	100 ppm	500 ppm	N/E	No	100 ppm	N/E	200 ppm	N/E
2. Petroleum Asphalt	5 mg/m ^{3*}	N/E	N/E	No	5 mg/m ^{3*}	N/E	N/E	N/E
		N/E: Not Estab			sphalt Fume	5		
PERSONAL PROTECTIVE EQ					L DDODEDI	150		
BOILING POINT: 325 °F	3	ECTION 9: PHY		CHEIVIICA	AL PROPERI		OLLINAE, NI/E	
	+la a 4 \	VAPOR DENSITY	r: >1 (air=1)			% VOLATILE BY VO		
EVAPORATION RATE: <1 (E	•	pH LEVEL: N/E	ADANCE: DI	alattatal		% VOLATILE BY W	•	
WEIGHT PER GALLON: 7.91	-	PRODUCT APPE		ack Liquid		VOC CONTENT: 2	-	
ODOR: Mild Organic	_	ODOR THRESHO	•			MELTING/FREEZII	NG POINT: N/D	
FLASH POINT: See Section 5	5	FLAMMABILITY	•			UEL/LEL: N/D		
VAPOR PRESSURE: N/D		RELATIVE DENS	•			SOLUBILITY: N/D		
PARTITION COEFFICENT: N	/D	AUTOIGNITION		•		DECOMPOSITION		: N/D
VISCOSITY: N/D				Not Deter		N/E: Not Establis	hed	
			10: STABIL					
STABILITY: Stable.		HAZARDOUS PO		_				
CONDITIONS AND MATERIA								
HAZARDOUS DECOMPOSITI		: Carbon monoxi	de, carbon di	oxide, oxi	des/compou	nds of nitrogen/sul	fur, and	
incomplete combustion pro	ducts.							
		SECTION 11:						
EYE CONTACT: Direct contact may cause mild to moderate irritation. Product vapors/mists may also cause irritation.								
SKIN CONTACT: Direct contact may cause slight skin irritation. Prolonged/repeated contact may result in irritation/dermatitis.								
INHALATION: Exposure may cause irritation of the nose, throat, respiratory tract, and other mucous membranes. Exposure to								
excessive vapor concentration		signs of transient	central nervo	ous system	depression	(headache, fatigue,	, drowsiness,	
dizziness, and loss of coordi	· ·							
INGESTION: May result in i		_	_	ion of exc	essive quanti	ties may result in s	ymptoms of	
transient central nervous system depression as noted above.								
SIGNS AND SYMPTOMS: Symptoms of eye irritation include tearing, reddening, and swelling. Symptoms of skin irritation								
	include redness and swelling. Gastrointestinal irritation symptoms include nausea, vomiting, and abdominal discomfort.							
Symptoms of respiratory irritation include runny nose, sore throat, coughing, chest discomfort, shortness of breath, and								
reduced lung function. Symptoms of transient central nervous system depression include: headache, fatigue, drowsiness,								
dizziness, and loss of coordi	dizziness, and loss of coordination.							
AGGRAVATED MEDICAL CONDITIONS: Pre-existing skin, eye, and respiratory disorders may be aggravated by exposure to								
this product.								
OTHER HEALTH EFFECTS: Some asphalts may possess weak carcinogenic activity. Occasional skin contact with petroleum								
asphalt is not expected to have serious health effects as long as good personal hygiene measures are followed.								
SECTION 12: ECOLOGICAL INFORMATION								
ECOTOXICITY:	N/E	DEG	RADABILITY:	N/E		BIOACCUMULATIN	/E POTENTIAL:	N/E
SOIL MOBILITY:	N/E	OTHER ADVE					Not Established	
SECTION 13: WASTE DISPOSAL INFORMATION								
WASTE DISPOSAL INFORMATION: Fuel blending/recycling facility. Product is a hazardous waste (D001).								
SECTION 14: TRANSPORTATION INFORMATION								
HAZARDOUS/NON-HAZARDOUS MATERIAL: Not regulated by DOT (Domestic Land Transportation).								
UN NUMBER: None.	1	HAZARD CLASS:	N/A	PACK	ING GROUP:	N/A		

UN PROPER SHIPPING NAME: N/A
ENVIRONMENTAL HAZARDS: None recognized. BULK TRANSPORTATION INFORMATION: None.

SPECIAL PRECAUTIONS: N/A: Not Applicable **SAFETY DATA SHEET**

Date of Preparation	: 10/26/21	Page 3 of 3	6320055
		SECTION 15: REGULATORY INFORMATION	
OTHER REGULATORY CONSIDERATIONS:		None recognized.	
		SECTION 16: OTHER INFORMATION	
PREPARATION DATE:	10/26/2021		
PREPARED BY:	Dave Carey		

The information contained herein is based on the data available to us and is believed to be correct. However, we make no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. We assume no responsibility for injury from the use of this product described herein.